

# Quattro3

MT301  
USB



Enhanced audio conferencing, *simplified.*

The Quattro3 (Q3) is a high-quality conference speakerphone that will turn any room into a professionally sounding conference room. It has an exceptionally large pickup and broadcasting range, yet is small in size and discrete in design. The Q3 utilizes multiple microphones, a uniquely designed speaker, and a powerful DSP to achieve commanding performance. The Q3 can easily be paired with an interface module to enable it to communicate with different types of infrastructures.

The MT301 is the basic model of the Q3 series. The USB outlet allows you to connect to the computer for any VoIP sessions, such as Skype, Vidyo, etc.

## FEATURES

- Four microphone beamforming array
- Full duplex communication
- Echo cancellation
- Noise suppression
- De-reverb filtering
- Automatic gain control
- Daisy chainable
- Interchangeable interface modules
- Durable aluminum casing
- LED lit control buttons



**THIS DEVICE PROVIDES AN IDEAL AUDIO SOLUTION FOR:**

- Small offices or home offices
- Small to very large conference rooms
- Classrooms and training rooms
- Webinars and web conferences
- Executive desktop

**Performance**

The Q3 has a new and more powerful DSP than before. We continue to deliver crystal clear audio through full duplex technology, giving you true High Definition Audio in your conference room.

**Design**

The unique design for this speakerphone makes it easy to use and hassle free. The cable connection is conveniently placed under the unit for discretion.

**Expandable**

All devices can be daisy chained. A total of 15 units can be chained with a standard Ethernet cable. No more proprietary cables. No more designated satellite units.

**Flexible**

The Q3 is the first conference phone that can adapt to the changes in your office. Instead of replacing your speakerphone as your voice system migrates to a different technology, you can simply replace the interface card on the unit. The interface can be installed using only two screws, making it versatile but simple to use.

**SPECIFICATIONS**

**Connections**

UBS interface (mini B connector)  
 3.5mm external loudspeaker and microphone jack  
 Volume Up / Volume Down buttons  
 Daisy chain expandability of up to 15 units  
 Power consumption: 5V 500mA peak through USB and wall mount AC/DC converted

**Audio**

Frequency response 50Hz – 16KHz  
 Low latency (10ms)  
 Broadcast level (peak): 92dB SPL @1m (5 watts RMS)  
 Noise cancellation > 10dB (without pumping noise)  
 100% full duplex – no attenuation (in either direction) during full duplex  
 High-end performance confirms to ITU-T G.167  
 Acoustic echo cancellation > 40dB with conversion speed of 40dB/sec  
 Residual echo is suppressed to the environment noise level, preventing artificial ducking of signal  
 4 high-quality directional microphones  
 Direction-finding algorithm (determines the presence and direction of a speaker)  
 Beamforming algorithm (forms and directs audio beams towards a defined direction)  
 Automatic voice-level adjustment (AGC)

**Dimensions**

Dimension: 7 in diameter  
 Height: 1-7/8 in  
 Weight: 1.75 lbs  
 Metal case and metal grill mesh for high RFI immunity and product durability

**Software**

Plug-and-Play - No installation or drivers.  
 Audio Setup Utility is available for Windows.  
 The Setup Utility helps monitor the audio input and output level but is not required.  
 Recording Utility is available for Windows.  
 Recording Utility allows you to record conversations to your computer via the device.  
 Operating systems: Windows 98 and up / Linux / MacOS

**Accessories**

USB cable  
 International AC adapter  
 Ethernet cable

**Warranty**

Two years

**Regulatory Compliance**

Complies with FCC 47 CFR Part 68, and ACTA adopted technical criteria: TIA-968-A  
 Complies with FCC 47CFR part 15; ICES-003: 2004 Issue 4, Class B; AS/NZS CISPR 22: 2006, Class B; EN 55022: 1998+A1(00)+A2(03), Class B; EN61000-3-2: 2000+A2(05); EN61000-3-3: 1995+A2(05); EN55024: 1998+A1(01)+A2(03)  
 Complies with ETSI EG 201 121 V1.1.3 (2000-02); ETSI ES 203 021-2 V2.1.2 (2006-01); ETSI ES 203 021-3 V2.1.2 (2006-01)  
 Conforms to the requirement of the European Union Directive 2002/95EC (RoHS Directive)



2934 N. Naomi St. • Burbank, CA 91504  
 Tel: (818) 937-4774 • Fax: (818) 230-9116