

Quadro[®]M26x



QuadroM26x: Small Business Hybrid PBX Solution

Many customers today require the latest VoIP technology but wish to retain their analog telephone investment. The QuadroM26x offers support for 26 analog devices and up to 80 IP phone extensions. In addition, this system supports SIP lines to connect to an internet service provider and eight FXO lines for a medium-size hybrid office environment. Any user on the system, whether they are on an IP or analog phone, will have access to the advanced VoIP features offered on the QuadroM26x. Even remote users will be able to take advantage of the cost-saving and performance-enhancing features.

The QuadroM26x is designed for offices up to 106 users but can offer performance and features usually only available on much larger enterprise products. These features include Automatic Call Distribution (ACD) for call centers, audio conferencing, call recording and barge-in features. Advanced features are purchasable items, so customers can choose what they pay for instead of being locked into a one-size-fits-all solution. Even though the QuadroM26x is designed for medium-size offices, the new owner can be comfortable knowing they are using an enterprise-grade solution backed by Epygi's support and guaranteed reliability.

True VoIP Hybrid Solution

Customers with either IP phones or analog devices demand the latest in telecommunications when purchasing a new PBX. Epygi has always focused on providing the leading edge technology for pure IP or mixed offices from eight users to small enterprises. As with all of our IP PBX solutions, any user of that system has access to the VoIP features, regardless of the endpoint.

Simple Migration Path

The QuadroM26x offers more FXS analog ports and with the addition of the Epygi QuadroFXS 16 gateway, the FXS port count can be even larger. As time continues, new users can be deployed as SIP extensions and eventually even the analog users could move to SIP.

What are Your VoIP BENEFITS?

- Hybrid Flexibility
- Easy Migration
- Latest SIP Technology
- Purpose-Built Appliance

Telephony

PBX Features

Call blocking, Forwarding, Hold, Transfer
 Call relay, Call waiting, Caller ID Detection
 Voice mail
 Call park, Pickup, Paging, Intercom
 Multi-level auto attendant with Interactive Voice Response (IVR) and VoiceXMLv2 support
 Voice mail with SMS notification
 Distinctive ringing
 Speed dialing
 Many extension ringing
 Receptionist
 Call hunting, Hiding Caller ID
 Automated Call back from Auto Attendant
 Hold music
 Call statistics
 Do Not Disturb
 Unified messaging
 3-way conferencing
 Hotline service
 T.38 fax, fax relay and clear channel fax
 Unified Fax Messaging
 Busy auto-redial
 Directory assistance
 Dial plans (call routing)
 Time of day routing
 Call Queue
 Voice Mail profile
 Automatic Call Distribution*
 Call Recording (20 ports) *
 Barge-in *
 Audio (32 ports)/Video (10 ports)
 Conference Server *

*Requires a software license key

Voice and Video Features

Voice Coding:

G.711, G.726 (16, 24, 32, 40 Kbps),
 G.729A, iLBC (13,33 kbit/s, 15,2 kbit/s);
 VAD, CNG, G.168 echo cancellation
 G.722 pass-through point-to-point HD call

Video Coding:

H.263 and H.264 pass-through point-to-point video call

VoIP Encryption:

SRTP

VoIP Signaling

SIP, SIP/TLS

DTMF

In band & out of band signaling support.

VoIP Data and Signaling Protocols

ITU-T G711, G.726, G729 Annex A;
 IETF RFC 3951- iLBC; ITU-T Q.23, Q.24;
 Bellcore GR.506, GR.181; ITU-T G.168-
 2000, 2002; ETS 300659_1,2,3;
 SIP, SIPS/TLS (RFCs: 2246, 3261, 3263,
 3265, 3311, 3323, 3324, 3325, 3428, 3515,
 3578, 3581, 3725, 3842, 3856, 3863, 3891,
 3892, 4028, 4235)
 SDP (RFC: 2327, 4568)
 RTP/SRTP (RFCs: 1889, 1890, 2833, 3389,
 3550, 3551, 3555, 3711, 4733, 3952),
 Fax over IP (ITU-T: T4, T30, T38, V17, V21,
 V27 ter, V29)

POTS Signaling

Loop start
 FSK and DTMF Caller ID support

POTS Signaling

Loop start, FSK and DTMF Caller ID support

DTMF

In band & out of band signaling support

Connectivity

Physical interfaces

Premise connections:

2 FXS short-loop FXS ports (RJ-11)
 24 FXS short-loop FXS ports (RJ-21)
 1 LAN Ethernet 10/100 BASE-T port (RJ-45)

Uplink connections:

8 FXO ports to the Central Office (RJ11)
 1 WAN Ethernet 10/100 BASE-T (RJ45)

Audio port connections:

Line-in/Line-out (Line-in Signal Level-
 0.5 V RMS, Line-out Load Resistance -
 600 Ohm to 10K Ohm)

Phones

IP phones:

16 SIP phones by default
 64 additional SIP phones may be added with feature keys
 All SIP phones can be connected both from LAN or WAN side
 Plug-and-Play with select IP Phone manufactures

Analog phones:

26 Analog phones (or other analog devices) to connect via FXS ports

Auto Attendants and Virtual Extensions

Auto Attendants:

Up to 200 standard and custom AA can be registered

Virtual Extensions:

Up to 200 Virtual Extensions can be registered**

**The total number of extensions used for IP phones, Analog phones, AA and virtual extensions can not exceed 200 extensions.

System Capacity

Up to 45 simultaneous VoIP calls with external parties
 Unlimited station to station calling for IP phones
 Unlimited station to station calling for analog phones
 8 analog PSTN calls with external parties

External Storage

Compact Flash

System

Management

Multilingual WEB interface accessible from LAN and WAN (HTTP/HTTPS) Password control
 Remote diagnostics and software upgrade
 Auto-provisioning
 VoIP Carrier Wizard
 Download/restore configuration
 Legible and editable configuration files
 Auto-configuration of IP phones via TFTP and HTTP
 SNMP Monitoring and Configuration
 Third Party Call Control XML RPC

Reset button with factory reset option

Custom Language Pack

Billing

Radius Client (RFCs: 2865, 2866)

Diagnostics/Testing

LEDs: Busy, Info, Fault, LAN, WAN,
 Loop settings
 Remote testing

Internet

STUN/NAT traversal (RFC 3489)

IPSec VPN with DES, 3DES and AES encryption in tunnel mode (RFCs: 2402, 2406, 2409). Manual and automatic IKE key support

PPTP VPN

L2TP VPN

Firewall security via:

Intrusion Detection System
 NAT (Network Address Translation)
 Policy and service-based filtering

Stateful inspection firewall

DHCP server on the LAN side

DHCP client on the WAN side

DNS server with forwarding functionality

SNTP (Simple Network Time Protocol) server/client for computer clock synchronization

PPPoE connection to the ISP with PAP/(MS)CHAP authentication

IP DIFFSERV for QoS

Virtual LAN (VLAN/IEEE 802.1Q)

Mail client to send voice and fax messages as e-mail attachments (.wav and .tif) and system notifications

DNS (DYNDNS) support with third party NAT/Router with port forwarding and port translation.

Environmental

Physical Dimensions

Rack-mountable devices:

Measurements: 19" x 7.56" x 1.77"

(48.0 x 19.2 x 4.5 cm)

Weight: 2.47 lbs.(1090 g)

Conditions

41°F - 104°F (5°C - 40°C) operating temperature

41°F - 140°F (5°C - 60°C) storage temperature

5% - 90% non-condensing humidity

Power Supply

Input 100 - 240 VAC; 50/60 Hz; 0.5 A

Regulatory Compliance

Telecom: TBR12/TBR13; AS/ACIF

Epugi Technologies, Ltd.
 6900 Dallas Parkway, Suite 850
 Plano, Texas 75024
 Tel/Fax: (+1)972.692.1166
 Web: www.epugi.com
 E-mail: sales@epugi.com

please contact