

# VoIP Gateway SVG6008

VoIP Gateway SVG6008 is designed for voice and fax services in IMS/soft-switch network of Telecom Carrier or VOIP service provider's network. It follows SIP/MGCP/H.248 protocol.

SVG6008 offers 8 analog FXS ports to meet different needs of users. With the priority of forwarding voice packages, it can provide excellent QoS.



## Features

- **Communication Protocol** Follows SIP/MGCP/H.248 protocol
- **QoS Guarantee** The port-based priority control makes voice packages transmitted first to provide excellent QoS
- **High Quality Voice** Supports multiple voice quality techniques, such as dynamic voice jitter buffer, VAD, CNG, echo sound offset and packet loss compensation, to provide high-quality voice as that of traditional telephones

## Specifications

<b>Model</b>	<b>SVG6008</b>
Protocol	SIP RFC3261 MGCP H.248 SDP RFC2327 RTP/RTCP
SIP	SIP Trunk SIP Register
Codec	G.711A/G.711U/G.723.1/G.729A/G.729AB
Voice	G.165/G.168 echo cancellation
Enhancement	Dynamic Jitter Buffer VAD/CNG Packet Loss Compensation
DTMF	In-Band DTMF / RFC2833 / SIP Info

FAX	T.38 T.30
Network	Static IP / DHCP Client / DNS / SNTP
QoS	802.1Q VLAN 802.1p Priority IP Tos
NAT Traversal	Static NAT Configure SIP Keep Alive Register STUN
Configuration	WEB Browser Console/Telnet
Firmware Upgrade	FTP / HTTP
Network Interface	Four 10/100Mbps Auto-negotiation RJ45 ports supporting Auto MDI/MDIX
Analog Interface	8* FXS(RJ11)
Power	AC adapter input: 100~242AC, 48/60Hz Consumption: <50W
Environmental Conditions	Operating temperature: 0° C~40° C Storage temperature: -20° C~60° C Humidity: 20~90%, non-condensing
Dimensions and Weight	Size:250(W) × 47(D) × 188 (H) mm Net Weight: 1.8kg

## Applications

