




Diva™ Server V-BRI

Most peoples' interaction with PCs is text-based such as email and instant messaging, but human voice is still the most natural way of communicating. Advances in speech recognition technologies and the ubiquity of fixed and mobile telephones now opens up a new world of opportunities for voice based systems.

The Ultimate Voice, Speech and Conferencing Platform

Diva Server V-BRI adapters are key building blocks for enabling these new breeds of voice business applications. Based on the latest PCI standards, each adapter provides connectivity to the telephony network via one ISDN Basic Rate (BRI) interfaces. Powerful Digital Signal Processors (DSP) – one dedicated to each communication channel - ensure real-time voice processing reducing system latency and improving overall system performance. An open and well documented application programming interface (API) combined with support for a broad range of operating systems facilitates development of leading-edge voice business applications.



Key Benefits

World-Class Voice Processing

Diva Server V-BRI adapters provide a full set of voice processing functions including tone detection and generation, voice activity detection and echo cancellation. Handling voice either in PSTN standard coding or in compressed coding allows adaptation to any kind of telephony system. Onboard DSPs perform these complex operations in real-time enhancing overall system performance and lowering implementation cost.

Facilitates Speech-Enabled Applications

Thanks to supporting full-duplex voice channels, callers can use an application-friendly feature known as "Barge-In". This allows a caller to interrupt speech prompts by speaking over them thereby controlling the pace of the conversation for a more pleasant user experience and better platform utilization. Enhanced echo cancellation and voice activity detection improve recognition accuracy and make better use of host platform resources.

Enhanced Switching and Conferencing Support

Diva Server V-BRI adapters support line interconnection and conferencing of calls on a single board as well as across boards within a server. Automatic gain control (AGC) is provided to automatically adjust the signal level of incoming calls for recording at normal levels.

Robust Voice Over IP (VoIP) Technology

For integrating established voice, speech and conferencing applications with emerging IP-Telephony clients and IP-Phones, Diva Server V-BRI provides key enabling features such as voice packetization into real-time transport protocol (RTP), voice compression (G.726 and GSM), adaptive jitter buffer and comfort noise generation.

Supports Best-of-Breed Applications

The support of standardized software interfaces such as CAPI 2.0 or TAPI as well as an open API (Diva Server SDK) facilitate the development of voice business applications. Common applications include voice portals, speech enabled interactive voice response (IVR) systems and media servers.

Superior Scalability and Flexibility

Up to eight Diva Server adapters - offering 2 to 240 channels - can be installed and operated concurrently in a single server. Any type of Diva Server adapter whether Analog, ISDN BRI, ISDN PRI, or E1/T1 can be mixed and matched.

Easy to Install

Diva Server V-BRI adapters conform to Intel and Microsoft Plug and Play standards, eliminating the need to manually configure the server.

Technical Specifications

Hardware:	<ul style="list-style-type: none"> Active ISDN adapter for Basic Rate Interface (BRI) Bus type: PCI rev. 2.2 (3.3V / 5V) 32-bit RISC CPU, 100 MHz, 131 MIPS 8 MB onboard SDRAM Scaleable to 8 adapters per system I/O Addresses and Interrupt are placed by the system Production Quality: ISO 9002 	<ul style="list-style-type: none"> Plug and Play Interface RJ45 Connector 2 x 65 MHz, 65 MIPS DSP Form factor: Max size of a low profile adapter (as defined by PCI 2.2 specification) Power Down Management 5 year warranty
Power Consumption and Environmental	<ul style="list-style-type: none"> Power consumption: 330 mA @+5 V typ. Operating humidity: 10% to 85% (non-condensing) Operating temperature: 10°C to 70°C Storage temperature: 0°C to 70°C Maximum tolerance in power supply variation: -5% to +5% 	
Driver Software	<ul style="list-style-type: none"> Supported operating systems: - Microsoft: Windows 2000, Windows XP, Windows Server 2003, including 64-Bit Editions. - Linux: Red Hat, SuSE and Debian distributions D-Channel and Signaling Protocols: ETSI-DSS1 (Euro-ISDN), NI-1 (North America National ISDN 1), 1TR6 (Germany), NET3 (Belgium), VN3/4/6 (France), 5ESS (AT&T), 5ESS (Lucent), DMS100 (Nortel), INS-64 (Japan), Australia on-ramp, Q-SIG, External Signaling (transparent D-channel), Network Termination (NT Mode) B-Channel Protocols: Transparent HDLC, Transparent Voice, Synchronous PPP and MLPPP, X.75 (LAPB), X.75/V.42 bis, LAPD, T.30, T.90NL, T.70NL, V.120, X.25, X.31, Rate adaption (56 kbps), V.90, V.42, V.42bis, V.110, V.120, PIAFS 1.0 / 2.0, SDLC Application Interfaces: - Microsoft: WAN Miniport, COM Port, CAPI 2.0, TAPI, Diva Server API (SDK) - Linux: TTY, CAPI 2.0, Diva Server API (SDK) Diagnostic Tools: B-channel and D-channel trace program M-Adapter Feature (patent pending): Combined Virtual Adapter, Internal Call Transfer, Explicit Call Transfer Emulation 	
Voice, Speech and Conferencing Features:	<ul style="list-style-type: none"> DTMF/MF transmission, detection and generation Voice Activity Detection Generic Tone detection and generation Fax signal detection Full duplex voice 'Barge-In' G.168 echo cancellation, up to 32 ms tail length Pitch Control Audio Tap ISDN Supplementary Services <ul style="list-style-type: none"> Number identification services (CLIP, CLIR, COLP, COLR, KEY, MSN, DDI, SUB) Call offering services (TP, CFU, CFB, CFNR) Call completion services (CW, HOLD, ECT) Charging Services (AoC) Three-party conference Large Conference 	<ul style="list-style-type: none"> Special Information Tone (SIT) detection DTMF Clamping and Filtering Silence Detection Automatic Gain Control (AGC) Cross board switching On-board switching and conferencing via line interconnect (call tromboning) VoIP support <ul style="list-style-type: none"> G.711 voice codec (64 kb/s, μ-law, A-law) G.726 voice codec (32 kb/s) GSM voice codec (13 kb/s) G.168 echo cancellation, up to 32 ms tail length Adaptive jitter buffer Voice activity detection (VAD) Comfort noise generation (CNG) Real Time Protocol (RTP framing)

Ordering Information

Product Name	Product Code
Diva Server V-BRI-2	306-219

National variants might be available. Please contact the Eicon Networks office in your region or look at www.eicon.com for further information.

