

## Algo 8201 IP PoE Intercom



Product Name: Algo 8201 IP PoE Intercom

Manufacturer: Algo

Model Number: Algo-8201

### Algo 8201 IP PoE Intercom

The Algo 8201 SIP PoE Intercom serves as an IP doorphone, facilitating hands-free communication with visitors at secure entrance doors, gates, access points, and in-room intercom scenarios. This outdoor-rated intercom is fully compliant as a 3rd party SIP endpoint, ensuring its compatibility with a wide range of hosted/cloud and premise-based VoIP telephone systems.

Algo 8201 Key Features:

- Secure SIP using TLS and SRTP.
- Wideband HD voice for high intelligibility speech.
- Initiates or accepts intercom calls.
- Outdoor rated – conformal coated electronics.

Presenting the Algo 8201 SIP PoE Intercom: a versatile IP doorphone with a backlit call button for easy communication. Seamlessly activated via a telephone keypad, it suits room intercoms and secure access points like hospitals, classrooms, and data centers. Configurable through a user-friendly web interface or auto-provisioning, it's powered by PoE (IEEE 802.3af) for reliable performance..

### Algo-8201 Technical Specifications

#### Power Input

- PoE IEEE 802.3af
- Nominal 2W Max 8W

#### Network Connection

- Female RJ45 Jack

#### SIP

- UDP, TCP, TLS, RTP, SRTP

#### Multicast

- Receive 50 zones IGMP, RTP

#### Audio Codecs

- G.711 A-law, G.711 u-law, G.722 Wideband

#### Configuration

- Web interface or provisioning server

#### Web Interface

- HTTP, HTTPS

#### Provisioning

- TFTP, FTP, HTTP, HTTPS

## Algo 8201 IP PoE Intercom

- DHCP Options 66, 150, 160
- Reboot via SIP check-sync

### Networking

- IPv4, DHCP, VLAN, MDNS
- Link Layer: LLDP, CDP
- QoS: DSCP
- Supervision: SNMP V3
- NAT: STUN, TURN, CRLF Keep Alive

### SIP Outbound

- Address Resolution: DNS, SRV Record
- Redundancy: Secondary and tertiary SIP server
- Time: NTP Server (up to four)
- API: RESTful API (contact Algo for custom applications)

### Enclosure

- High impact UV stabilized flame retardant plastic with stainless steel (8201) or anodized aluminum (8203) faceplate

### Button Functions

- Call SIP Extension

### Speaker

- Weatherproof mylar 3W Neodymium magnet

### Microphone

- Omnidirectional

### Hands-Free

- Non-blocking two-way voice

### Audio Memory

- 1 GByte audio storage

### Relay Output

- NO, C, NC contacts rated 50 mA 30 V MAX. For resistive loads or solenoid with snubber, the contacts may switch up to 1 Amp.

### Door Sensor Input

- Max 6.5 kOhm external resistance. Selectable NC or NO input

### Secure Door Control

- Supports optional 8063 IP Door Controller

## Algo 8201 IP PoE Intercom

### Environmental

½ Outdoor IP66 -40 to +122 deg F (-40 to +50 deg C)

### Dimensions

½ 4.5" W x 4.5" H x 1.2" D

½ 11.5 cm W x 11.5 cm H x 3.0 cm D

### Mounting

½ Flush or surface mount in a 2-gang electrical box. The 8201 includes a plastic bezel for surface mounting as a convenience. Surface mounting the 8203 requires an electrical box such as the Algo 3100 to accommodate conduit.

### Regulatory Compliance

½ EN60950:2001, IEEE 802.3-2008, RoHS, CE, FCC Class A, CISPR 22 Class A, CISPR 24, CSA/UL (USA & Canada)

**Price: £378.80**

---