

# Algo 1128I - Algo Clear LED Strobe Light



Product Name: Algo 1128I - Algo Clear LED Strobe Light

Manufacturer: Algo

Model Number: Algo-1128I

Algo 1128 Analog Strobe Light

The Algo 1128 24V Aanlong Straobe Light serves as a clear/white visual alert for telephone ringing, specifically addressing noise sensitivity or hearing impairment concerns. Additionally, it is widely utilized for safety, security, and emergency event notifications.

Algo-1128 Analog Strobe Light Key Features:

i¿½ Strobe Alert Notification System utilizing analog technology.

تزير Long-life LEDs with 360 x 180 degree visibility from wall/ceiling mount.

� 34+ years of continuous use with zero light degradation.

រី¿½ Rated at 643 lumens with a maximum luminous intensity of 198 candela

The 1128 can be activated through an analog station / FXS port or ATA. It can also be triggered by dry contact closure input or auxiliary input detection of 3-30V AC or DC. Moreover, it supports audio detection from the Algo 1825PM Duet Plus analog loud ringer.

Algo-1128 Technical Specifications

Power

Ti21/2 Power input: 12VDC 750 mA or 24VDC 375 mA
Ti21/2 Power supply shipped: AC Mains Adapter 120V/230V

#### Optical

� 8 LEDs (White)� 16 Selectable flash patterns using 4 position switch� 198 Cd� 643 Lumens

### Input/Output

� Relay Input: Max 1 kOhm

� Ring Input: 20/25 Hz 20Vrms minimum � Auxiliary Input: 3-30V DC or AC (rms)

#### Environmental & amp; Mechanical

ī¿½ Environmental: -20 to +50° C (-4 to +122° F); 10-95% RH, non-condensing. Dry indoor location only unless wiring cavity protected from water ingress using supplied gaskets or other protective measures.

T¿½ Dimensions (Product): 4.8″ x 4.8″ x 3″ (12.2cm x 12.2cm x 7.6cm)

آذِرًا Weight (Product): 1.0 lbs (0.5 kg) / Weight (Shipping): 1.7 lbs (0.8 kg)

#### Compliance

آز½ RoHS, CE, FCC, CSA/UL (USA & amp; Canada), EN60950



## Algo 1128I - Algo Clear LED Strobe Light

Price: £350.60