

Grandstream GWN7701P Unmanaged Network Switch



Product Name: Grandstream GWN7701P Unmanaged Network Switch

Manufacturer: Grandstream

Model Number: GWN7701P

Grandstream GWN7701P Unmanaged Network Switch

The Grandstream GWN7700 series introduces unmanaged network switches, providing a cost-effective method to add high-speed Gigabit connectivity to home offices and small/medium businesses. These switches require no configuration, offering a desktop or wall-mountable design with auto MDI/MDIX to eliminate crossover cable needs. Each port supports auto-negotiation, allowing compatibility with 10/100/1000Mbps devices.

Grandstream GWN7701P Key Features:

- 8x RJ45 Ports for Gigabit connectivity.
- Green tech reduces power use.
- LED Indicators for Link, Activity, Speed, and Power.
- Auto MDI/MDIX for all ports.
- Storm Control (fixed to 100Mbps) for traffic monitoring.
- QoS: Supports Default Strict Priority (when present).

In summary, the GWN7700 series of unmanaged network switches efficiently enhances connectivity. Its features like auto MDI/MDIX, and auto-negotiation cater to diverse networking needs, making it an ideal choice for various setups.

Grandstream GWN7701P Technical Specifications

General

- 8x 2.5 gigabit ports
- PoE ports: 4
- Enclosure: metal
- Mount: desktop/wall mount

Standards and Protocols

- IEEE 802.3i
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3x
- IEEE 802.1p
- IEEE 802.3af
- IEEE 802.3at

Port Features

- 8x 10/100/1000Mbps RJ45 Ports
- AUTO Negotiation
- AUTO MDI/MDIX

Network Media

- 1000Base-T/100Base-TX/10Base-T, Half/Full-Duplex

PoE Configuration

- 1-4 Ports 802.3 af/at compliant
- Up to 30 W on Each Port, Total 60W Power Budget

Grandstream GWN7701P Unmanaged Network Switch

• Overload to cut off the lowest priority port
• Priority: Port 4 to Port 1

LED Indicators

• Per port: Link/Activity Green
• Per device: Power Green

Mac Address Table

• 8K entries

Switching Capacity

• 16Gbps

Jumbo Frame

• 9KB

Advanced Features

• Mac Address Auto-Learning And Auto-Aging
• IEEE 802.3x Flow Control
• 802.1p/DSCP QoS
• Unlink clear FDB Feature
• IGMP:

• IGMP Fast-Leave
• IGMP Snoop
• Route Port Autolearn
• Query Refresh Member Port

Power Adapter

• External 48-53.5VDC/1.22A

Max Power Consumption by Base System

• 3W (excluding PoE output power)

Environmental

• Operating Temperature: 0 to 40 °C (32 to 104 °F)
• Storage Temperature: -20 to 60 °C (-4 to 140 °F)
• Operating Humidity: 10% to 90% Non-condensing
• Storage Humidity: 10% to 90% Non-condensing

Dimensions (L x W x H)

• Unit: 190 x 100 x 28mm
• Package: 230 x 210 x 51mm

Grandstream GWN7701P Unmanaged Network Switch

Weight

1 Unit: 0.44KG

Entire Package: 0.92KG

Package

1x Switch

1x Power Adapter

1x Quick Installation Guide (QIG)

Compliance

FCC

CE

RCM

IC

UKCA

Price: £39.10
