

Grandstream GWN7702P Unmanaged Network Switch



Product Name: Grandstream GWN7702P Unmanaged Network Switch

Manufacturer: Grandstream

Model Number: GWN7702P

Grandstream GWN7702P Unmanaged Network Switch

The Grandstream GWN7700 series introduces unmanaged network switches, providing a cost-effective method to add high-speed Gigabit connectivity to home offices and small/medium businesses. These switches require no configuration, offering a desktop or wall-mountable design with auto MDI/MDIX to eliminate crossover cable needs. Each port supports auto-negotiation, allowing compatibility with 10/100/1000Mbps devices.

Grandstream GWN7702P Key Features:

- 8x PoE+ output.
- Green tech reduces power use.
- LED Indicators for Link, Activity, Speed, and Power.
- Auto MDI/MDIX for all ports.
- Storm Control (fixed to 100Mbps) for traffic monitoring.
- QoS: Supports Default Strict Priority (when present).

The GWN7700 series of unmanaged network switches efficiently enhances connectivity. Its features like auto MDI/MDIX, and auto-negotiation cater to diverse networking needs, making it an ideal choice for various setups.

Grandstream GWN7702P Technical Specifications

General

- 16x 2.5 gigabit ports, (8x PoE ports)
- Enclosure: metal
- Mount: Desktop/Rack mount

Standards and Protocols

- IEEE 802.3i
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3x
- IEEE 802.1p
- IEEE 802.3af
- IEEE 802.3at

Port Features

- 16/24x 10/100/1000Mbps RJ45 Ports
- AUTO Negotiation
- AUTO MDI/MDIX

Network Media

- 1000Base-T/100Base-TX/10Base-T, Half/Full-Duplex

PoE Configuration

- 1-8 Ports 802.3 af/at compliant
- Up to 30 W on Each Port, Total 138W Power Budget;
- Overload to cut off the lowest- s priority port.

Grandstream GWN7702P Unmanaged Network Switch

• Priority: Port 1 to Port 8

LED Indicators

• Per port: Link/Activity Green
• Per port: PoE output - Yellow
• Per device: Power Green

Mac Address Table

• 8K entries

Switching Capacity

• 32Gbps

Jumbo Frame

• 10KB

Advanced Features

• Mac Address Auto-Learning And Auto-Aging
• IEEE 802.3x Flow Control
• Half duplex backpressure

Power Adapter

• Internal 100-240V AC, 50/60Hz, 150W

Max Power Consumption by Base System

• 10.1W@220V/50Hz (excluding PoE output power)

Environmental

• Operating Temperature: 0 to 40 °C (32 to 104 °F)
• Storage Temperature: -20 to 60 °C (-4 to 140 °F)
• Operating Humidity: 10% to 90% Non-condensing
• Storage Humidity: 10% to 90% Non-condensing

Dimensions (L x W x H)

• Unit: 280 x 180 x 44mm
• Package: 366 x 211 x 53mm

Weight

• Unit: 1.58KG
• Entire Package: 2.18KG

Package

• 1x Switch
• 1x 1.2m AC Cable

Grandstream GWN7702P Unmanaged Network Switch

- 1x Quick Installation Guide (QIG)
- 1x Rack-mounting Standard Brackets
- 4x Rubber Feet

Compliance

- FCC
- CE
- RCM
- IC
- UKCA

Price: £98.80
