

Yealink DECT Deployment Kit

Product Name: Yealink DECT Deployment Kit

Manufacturer: Yealink

Model Number: DECT Deployment Kit

Yealink DECT Deployment Kit

The Yealink DECT IP multi-cell deployment toolkit is an all-inclusive solution to facilitate the deployment and administration of multi-cell DECT IP systems. This toolkit is specifically engineered to streamline the establishment and arrangement of extensive DECT deployments, suitable for settings like office complexes, storage facilities, or corporate surroundings. Yealink DECT Deployment Kit Key Features:

� DECT Manager

� Automatic Provisioning

ï¿1/2 Scalability and Flexibility

� Coverage Planning

The DECT IP Multi-Cell Deployment Toolkit offers a comprehensive approach to oversee extensive DECT deployments. It simplifies the process of setting up, configuring, and continuously administering DECT systems, equipping administrators with the necessary resources to enhance coverage, guarantee call quality, and uphold communication network security. It is important to note that the specific features and capabilities of the toolkit may vary based on the version and configuration of the Yealink DECT system being used.

This kit contains:

� DTK (Measuring Base Station)

ï¿1/2 W56H Handset (2)

� Battery Cover (2)

� Rechargeable Battery (4)

� USB Charging Cradle (2)

� Power Adapter (2)

تز½ Stand

ï¿1/2 Base Station Clip

ï¿1/2 Mobile Power Clip

ï¿⅓ USB-DC Cable

ï¿1/2 UH33 Headset (2)

� Notebook and Pen

ï¿1/2 Quick Start Guide

Yealink W56H - Technical Specifications Display

� 2.4'' 240x320 pixels colour display

ī¿½ Intuitive user interface with icons and soft keys

� Caller ID with name and number

าั¿½ Notification Light: voice mail and missed call is signaled via display and illuminated power indicator

i¿½ Date & Date & Ime (manual or auto synchronised)

� Screen Saver

� Multiple languages

آذِ LCD backlit

ï¿1/2 Key backlit



Yealink DECT Deployment Kit

Phone Features

- ï¿1/2 Up to 2 simultaneous calls per handset
- ï¿⅓ Handset select for receiving call
- ï¿1/2 Handset and Number select for making call
- � Auto intercom, Auto answer
- � Call hold, Call transfer
- � Switching between calls
- ï¿⅓ 3-way conference
- ï¿1/2 Call waiting, Mute, DND
- � Redialling of last 20 numbers entered
- � Call forward (Always/Busy/No Answer)
- آذِ1/2 Speed dial, Voicemail, Silence
- آزئ 100 phone book memory (store in the base)
- ï¿⅓ Remote phonebook
- � Phonebook search, Black list
- � Call Log(Outgoing/Missed/Accepted)
- � Direct IP call without SIP proxy
- � Reset to factory, Reboot
- � Keypad lock, Emergency call
- � Anonymous call
- � Anonymous call rejection

Voice Features

- ï¿⅓ Full-duplex speakerphone
- � Receiver volume control: 5 steps
- ï¿1/2 Ringer volume control: 5 steps+off
- ï¿⅓ 9 ringer melodies
- � Multiple advisory tones
- � Acoustic warning for low battery status
- ï¿⅓ DTMF

Connectors and Management

- � Headset jack (3.5 mm)
- � Handset upgrade: OTA (Over-The-Air)

Yealink UH33 - Technical Specifications Main Features

- � Supports SIP-T41S/T42S/T46S/T48S/T53/T53W/T54W/T57W/T58A/VP59
- ī¿1/2 For T41S/T42S/T46S/T48S: upgrade to the version 82 or higher
- าั¿1/2 USB and 3.5mm connectivity to laptop and smart device
- ï¿1/2 Simple call management via control unit
- า๊¿½ Integrated LED indicator and warning tone
- تزير ActiveProtection technology safeguards users from acoustic injury
- រី¿½ HD Voice/Wideband speaker performance and noise cancellation
- ī¿½ 330° bendable boom arm for easy adjustment without breaking

General

- 12/2 Cord length: HS cable: 1.2m; Control cable: 0.9m
- � Connection: 3.5mm jack, USB 2.0



Yealink DECT Deployment Kit

ī¿½ Supported operating systems: Microsoft Windows®, Apple Mac OS

� Color: Black

Microphone

าั¿½ Microphone type: Noise-cancelling าั¿½ Frequency response range: 100-8kHz าั¿½ Microphone bandwidth: Wideband

ï¿1/2 Microphone Sensitivity: -38.0 dB re. 1V/Pa

Speaker

� Speaker type: 90±15%Ω � Frequency response range: 112Hz-8.5kHz

ï¿1/2 Speaker bandwidth: Wideband

� Speaker Sensitivity: 96dB SPL+/-3dB SPL � Speaker Impedance: 90±15% � Speaker input power: normal: 20mW; Max: 80mW

Control unit

� Answer/End a call � Volume up/down

� Microphone mute

ï¿1/2 Redial last outgoing call

ï¿⅓ Reject incoming call

Price: £531.90