

Grandstream GWN7811P Managed Network Switch



Product Name: Grandstream GWN7811P Managed Network Switch

Manufacturer: Grandstream

Model Number: GWN7811P

Grandstream GWN7811P Managed Network Switch

The GWN7810 series are Layer 3 managed network switches that allow medium-to-large enterprises to build scalable, secure, high performance and smart business networks that are fully manageable.

Grandstream GWN7811P Key Features:

- 8 Gigabit Ethernet ports and 2 10Gigabit SFP+ ports
- Smart power control to support dynamic PoE/PoE+ power allocation per port for the PoE models
- Supports deployment in IPv6 and IPv4 networks
- ARP Inspection, IP Source Guard, DoS protection, port security & DHCP snooping
- Embedded controller to manage switch; GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise network management platform
- Built-in QoS allows for prioritization of network traffic

The series is also supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise network management platform.

Grandstream GWN7811P Technical Specifications
Network Protocol

- IPv4
- IPv6
- IEEE 802.3
- IEEE 802.3i
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3z
- IEEE 802.3ae
- IEEE 802.3x
- IEEE 802.3af/at/bt
- IEEE 802.1p
- IEEE 802.1Q
- IEEE 802.1w
- IEEE 802.1d
- IEEE 802.1s
- IEEE 802.3az
- IEEE 802.3ad
- IEEE 802.3AB
- IEEE 802.1p
- IEEE 802.1D
- IEEE 802.1x

Gigabit Ethernet Ports

- 8

10Gigabit SFP+ Ports

- 2

Grandstream GWN7811P Managed Network Switch

Note: Supports DAC cable, and must be \leq 5m
Maximum no. of Supported Modules

$\frac{1}{2}$ SM-10G: 2
 $\frac{1}{2}$ MM-10G: 2
 $\frac{1}{2}$ RJ45-10G: 2

Console

$\frac{1}{2}$ 1

of PoE Ports

$\frac{1}{2}$ 8

Link Aggregation

$\frac{1}{2}$ 5

Max Output Power per PoE Port

$\frac{1}{2}$ 30W

Max Total PoE Output Power

$\frac{1}{2}$ 120W

PoE Standards

$\frac{1}{2}$ IEEE 802.3af/at

Auxiliary Ports

$\frac{1}{2}$ 1x Reset Pinhole

Forwarding Mode

$\frac{1}{2}$ Store-and-forward

Total non-blocking throughput

$\frac{1}{2}$ 28Gbps

Switching Capability

$\frac{1}{2}$ 56Gbps

Forwarding Rate

$\frac{1}{2}$ 41.644Mpps

Packet Buffer

$\frac{1}{2}$ 12MB

Grandstream GWN7811P Managed Network Switch

Switching

- 16K static, dynamic and filtering MAC addresses
- 4K VLANs, port-based VLAN, IEEE 802.1Q VLAN tagging, voice VLAN
- VLAN virtual interface
- GVRP (pending)
- Spanning tree, 32 instances for STP/RSTP/MSTP

Routing

- Static routing
- Dynamic routing, including RIP, RIPng, OSPF and OSPFv3
- Policy routing (pending)

Multicast

- IGMP Snooping
- MLD Snooping
- MVR (pending)

QoS/ACL

- Port priority
- Priority mapping
- Queue scheduling, including SP, WRR, WFQ, SP-WRR and SP-WFQ
- Traffic shaping
- Rate limit
- 2K ACL for Ethernet, IPv4 and IPv6

DHCP

- DHCP server, DHCP relay, DHCP Option 82, 60, 160 and 43

Maintenance

- CPU and memory monitoring
- SNMP
- RMON
- LLDP&LLDP-MED
- Backup and restore
- Syslog
- Diagnostics including Ping, Traceroute, port mirroring, UDLD (TBD) and copper test

Security

- User hierarchical management and password protection, HTTPS, SSH, Telnet
- 802.1X authentication
- AAA authentication including RADIUS, TACACS+
- Storm control
- Port isolation, port security, sticky MAC
- Filtering MAC address
- IP source guard, DoS attack prevention, ARP inspection
- DHCP Snooping
- Loop protection including BPDU protection, root protection (pending) and loopback protection (pending)

Grandstream GWN7811P Managed Network Switch

• Kensington Security Slot (Kensington Lock) support

Mounting

• Desktop, Wall-Mount, or Rack-Mount (rack-mounting kits included)

System LEDs

• 1x tri-color LED for device tracking and status indication

Data Transferring LEDs

• 10x green-color LEDs

PoE Powered LEDs

• 8x yellow-color LEDs

Environmental

• Operation: 0°C to 45°C, humidity 10-90% RH (Non-condensing)

• Storage: -10°C to 60°C, humidity: 5% to 95% RH (Non-condensing)

Dimensions

• 330mm (L) x 176mm (W) x 44mm (H)

• 440mm (L) x 200mm (W) x 44mm (H)

• 440mm (L) x 300mm (W) x 44mm (H)

Unit Weight

• 2.17Kg

Package Content

• 1x Switch

• 1x 1.2m (10A) AC Cable

• 1x 25cm Ground Cable

• 4x Rubber Footpads

• 1x Power Cord Anti-Trip

• 8x Screws (KM 3*6)

• 1x Quick Installation Guide

• 1x Console Cable (Optional)

• 2x Extended Rack-Mounting Kits

Compliance

• FCC

• CE

• RCM

• IC

• UKCA

Grandstream GWN7811P Managed Network Switch

Price: £160.00
