



Product Name: Grandstream GWN7811P Managed Network Switch

Manufacturer: Grandstream Model Number: GWN7811P

Grandstream GWN7811P Managed Network Switch

The GWN7810 series are Layer 3 managed network switches that allow medium-to-large enterprises to build scalable, secure, high performance and smart business networks that are fully manageable.

Grandstream GWN7811P Key Features:

าั¿½ 8 Gigabit Ethernet ports and 2 10Gigabit SFP+ ports

าั¿½ Smart power control to support dynamic PoE/PoE+ power allocation per port for the PoE models

� Supports deployment in IPv6 and IPv4 networks

าั¿½ ARP Inspection, IP Source Guard, DoS protection, port security & Tiber Source Guard, DoS protection, DoS protection,

าั¿½ Embedded controller to manage switch; GWN.Cloud and GWN Manager,

Grandstream's cloud and on-premise network management platform

าั¿½ Built-in QoS allows for prioritization of network traffic

The series is also supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise network management platform.

Grandstream GWN7811P Technical Specifications

Network Protocol

� IPv4

ï¿1/2 IPv6

� IEEE 802.3

ï¿⅓ IEEE 802.3i

ï¿1/2 IEEE 802.3u

ï¿⅓ IEEE 802.3ab

ï¿⅓ IEEE 802.3z ï¿⅓ IEEE 802.3ae

ï¿1⁄2 IEEE 802.3x

ï¿1/2 IEEE 802.3af/at/bt

ï¿⅓ IEEE 802.1p

IEEE 802.1Q

ï¿⅓ IEEE 802.1w

ï¿⅓ IEEE 802.1d

ï¿1/2 IEEE 802.1s

ï¿1/2 IEEE 802.3az

ï¿1/2 IEEE 802.3ad

ï¿1/2 IEEE 802.3AB

ï¿1⁄2 IEEE 802.1p

ï¿1/2 IEEE 802.1D

ï¿1/2 IEEE 802.1x

Gigabit Ethernet Ports

1;½ 8

10Gigabit SFP+ Ports

2 1⁄2 3/



Note: Supports DAC cable, and must be ≤ 5m Maximum no. of Supported Modules ï¿⅓ SM-10G: 2 ï¿⅓ MM-10G: 2 ï¿⅓ RJ45-10G: 2 Console 1 1⁄2 غ # of PoE Ports 8 1⁄25٪ Link Aggregation 5 ⅓غï Max Output Power per PoE Port � 30W Max Total PoE Output Power 120W ½ ئۆت PoE Standards ï¿1/2 IEEE 802.3af/at **Auxiliary Ports** � 1x Reset Pinhole Forwarding Mode ï¿1/2 Store-and-forward Total non-blocking throughput � 28Gbps **Switching Capability** ï¿⅓ 56Gbps Forwarding Rate ï¿1/2 41.644Mpps Packet Buffer

� 12MB



Switching

- � 16K static, dynamic and filtering MAC addresses
- ارۇ 1 4K VLANs, port-based VLAN, IEEE 802.1Q VLAN tagging, voice VLAN
- � VLAN virtual interface
- ï¿⅓ GVRP (pending)
- ï¿⅓ Spanning tree, 32 instances for STP/RSTP/MSTP

Routing

- آخ½ Static routing
- าั¿½ Dynamic routing, including RIP, RIPng, OSPF and OSPFv3
- � Policy routing (pending)

Multicast

- آز½ IGMP Snooping
- � MLD Snooping
- � MVR (pending)

QoS/ACL

- � Port priority
- ï¿⅓ Priority mapping
- าั¿½ Queue scheduling, including SP, WRR, WFQ, SP-WRR and SP-WFQ
- ï¿⅓ Traffic shaping
- ï¿⅓ Rate limit
- ï¿1/2 2K ACL for Ethernet, IPv4 and IPv6

DHCP

� DHCP server, DHCP relay, DHCP Option 82, 60, 160 and 43

Maintenance

- � CPU and memory monitoring
- ï¿⅓ SNMP
- ۳¿⅓ RMON % ال
- � LLDP&LLDP-MED
- � Backup and restore
- آزيٰ Syslog
- آذًا Diagnostics including Ping, Traceroute, port mirroring, UDLD (TBD) and copper test

Security

- Till User hierarchical management and password protection, HTTPS, SSH, Telnet
- � 802.1X authentication
- ï¿1/2 AAA authentication including RADIUS, TACACS+
- ï¿⅓ Storm control
- � Port isolation, port security, sticky MAC
- � Filtering MAC address
- า๊¿½ IP source guard, DoS attack prevention, ARP inspection
- ï¿⅓ DHCP Snooping
- ī¿½ Loop protection including BPDU protection, root protection (pending) and loopback protection (pending)



า๊¿½ Kensington Security Slot (Kensington Lock) support Mounting آذًا Desktop, Wall-Mount, or Rack-Mount (rack-mounting kits included) System LEDs � 1x tri-color LED for device tracking and status indication Data Transferring LEDs ï¿1/2 10x green-color LEDs PoE Powered LEDs ï¿1/2 8x yellow-color LEDs Environmental آذِرًا 2 Operation: 0° C to 45° C, humidity 10-90% RH (Non-condensing) าั¿½ Storage: -10°C to 60°C, humidity: 5% to 95% RH (Non-condensing) **Dimensions** � 330mm (L) x 176mm (W) x 44mm (H) � 440mm (L) x 200mm (W) x 44mm (H) � 440mm (L) x 300mm (W) x 44mm (H) Unit Weight � 2.17Kg Package Content تز½ 1x Switch ï¿1/2 1x 1.2m (10A) AC Cable � 1x 25cm Ground Cable ï¿1/2 4x Rubber Footpads ïز½ 1x Power Cord Anti-Trip ï¿1/2 8x Screws (KM 3*6) � 1x Quick Installation Guide � 1x Console Cable (Optional) � 2x Extended Rack-Mounting Kits

Compliance

� FCC � CE � RCM � IC � UKCA



Price: £135.50