Snom D140 Desk phone

Product Name: Snom D140 Desk phone
Manufacturer: Snom
Model Number: D140

Snom D140 Desk Phone
The Snom D140 is suitable for all work environments in which cost-effective but high-quality communication is required. The device, equipped with slate grey housing, offers all the important telephony functions.
Snom D140 Key Features

ï¿½ 2 SIP identities
ï¿½ Low power consumption
ï¿½ 2.8" TFT LCD - grayscale display
ï¿½ 360° notification display

Two freely programmable SmartLabel keys, six dedicated and four context-sensitive function keys are available for simple and intuitive operation. The D140 is ideal for large installations, e.g. in public administrations.
Snom D140 Technical Specifications
Basics

ï¿½ Product information

ï¿½ IP desk phone
ï¿½ PN 00004651
ï¿½ Colour: slate gray
ï¿½ Operating system: Linux

ï¿½ Placement: indoor, desktop, wall mounting

Dimensions and weight

ï¿½ Dimensions (L × W × H, approx.) without footstand

ï¿½ 205 mm × 185 mm × 40 mm

ï¿½ Dimensions (H x W x D, approx.) with footstand

ï¿½ 205 mm × 185 mm × 220 mm (high angle 46°)
ï¿½ 205 mm × 185 mm × 200 mm (low angle 28°)

ï¿½ Weight (approx.):

ï¿½ 710 g without footstand
ï¿½ 830 g with footstand

Display and indicators

ï¿½ Display

Snom D140 Desk phone

ï¿½ TFT liquid crystal display (LCD), graphical, grayscale, backlit
ï¿½ Size (diagonal): 2.8″ (67 mm)
ï¿½ Size (W × H): 59 mm × 33 mm
ï¿½ Resolution: 320 × 240 pixels

ï¿½ 3 LED indicators

ï¿½ Call status indication: 1 red LED
ï¿½ Function key status indication: 2 multicolour LEDs

Keypad and function keys

ï¿½ 36 hard keys in total
ï¿½ 12 keys (standard ITU telephone keypad)
ï¿½ 4 context-sensitive function keys
ï¿½ 5-way navigation key
ï¿½ 2 SmartLabel keys (with multicolour LED)
ï¿½ 5 dedicated audio keys

ï¿½ Mute, Speakerphone, Headset, Volume + / - (rocker)

ï¿½ 6 dedicated function keys

ï¿½ Ok, Cancel, DND, Message (with red LED), Directory, Menu, Transfer, Hold

ï¿½ Keyboard lock

Audio devices, codecs and features

ï¿½ Corded receiver:

ï¿½ Hearing aid compatible (HAC)

ï¿½ Audio codecs

ï¿½ G.711 (A-law, μ-law), G.722, G.726, G.729, GSM 6.10 (FR)

ï¿½ Dual-tone multi-frequency signaling (DTMF / RFC2833)

ï¿½ SIP-INFO, in-band, out-of-band

ï¿½ Related features

ï¿½ Built-in assignable ringtones
ï¿½ Comfort Noise Generator (CNG)
ï¿½ Voice Activity Detection (VAD)

Snom D140 Desk phone

Interfaces and connections

ï¿½ Power options

ï¿½ Power over Ethernet (PoE)
ï¿½ IEEE 802.3af, class 1 | IEEE 802.3az

ï¿½ Power adapter

ï¿½ 100 - 240 V AC, 50 - 60 Hz | 5 V DC (SELV), 2 A, 10 W

ï¿½ Wired interfaces

ï¿½ Power adapter:
ï¿½ 1 coaxial power connector (socket)
ï¿½ Ethernet 10/100 Mbit/s: 2 × RJ45-8P8C sockets
ï¿½ Corded receiver: RJ9-4P4C socket
ï¿½ Headset: 1 RJ9-4P4C socket
ï¿½ EHS adapter: 1 RJ12-6P6C (EHS) socket

ï¿½ Sensors

ï¿½ Hook switch sensor

See Datasheet for full Technical specification

Price: £47.25