

2N IP Verso Door Intercom - Combined Bluetooth & RFID Module (9155082)



Product Name: 2N IP Verso Door Intercom - Combined Bluetooth & RFID Module (9155082)

Manufacturer: 2N Telecommunications

Model Number: 9155082

2N IP Verso Door Intercom - Combined Bluetooth & STID Module (9155082) The 2N IP Verso Door Intercom 9155082 designed for 2N® IP Verso and 2N® LTE Verso integrates cutting-edge RFID technology with a contemporary access control system based on Bluetooth technology. This advanced module incorporates a multi-frequency RFID reader, capable of reading both less secure 125kHz cards and sophisticated 13.56MHz smart cards. Additionally, doors can be conveniently opened using a smartphone equipped with the 2N® Mobile Key application—users can either tap the button in the app or simply touch the reader.

2N IP Verso Door Intercom 9155082 Key Features:

� Reads majority of access cards on the market

� Open doors using a smartphone

ï¿⅓ Mobile credentials for free

This module not only enhances security through versatile RFID capabilities but also provides a convenient and modern access solution with the seamless integration of Bluetooth technology. The combination of these technologies ensures flexibility and ease of access control for a range of user preferences and scenarios.

2N IP Verso Door Intercom 9155082 Technical Specifications Bluetooth Reader

� Version- compatible with Bluetooth 5.0 (BLE)

تز½ Range

� Short - typically up to 3m* � Long - typically up to 10m*

* Distances should serve only as an approximate guide and may vary depending on the phone model and installation environment.

Security
ities RSA-1024 and AES-128 encryption
RX sensitivity

� up to -93 dBm

Mode

� Touch, tap in app, card

Mobile Application Support

าั¿1/2 Android 6.0 and higher, iOS 12.0 and higher

RFID Card Reader Supported frequencies



2N IP Verso Door Intercom - Combined Bluetooth & RFID Module (9155082)

� 125 kHz variant � 13.56 MHz variant � 125 kHz and 13.56 MHz variant

Supported card types

� Card type compatibility depends on Order No.

125 kHz

� EM4xxx

ї¿½ HID Prox – versions with 125 kHz support and S in Order No.

13.56 MHz

� ISO14443A, PicoPass (HID iClass), FeliCa, ST SR(IX), NFC (2N® Mobile Key) reads UID (CSN) and secured MIFARE® DESFire® EV2/EV3 cards using 2N® PICard technology

Secured 13.56 MHz

ϊ¿½ ISO14443A (MIFARE® DESFire®), PicoPass (HID iClass), FeliCa, ST SR(IX), NFC (2N® Mobile Key), HID SE (Seos, iClass, MIFARE SE) reads secured MIFARE® DESFire® EV2/EV3 cards using 2N® PICard technology reads PACs ID (HID iClass cards with SIO object)

Price: £465.60