

Fanvil i505 Android Indoor Station



Product Name: Fanvil i505 Android Indoor Station

Manufacturer: Fanvil Model Number: i505

Fanvil i505 Android Indoor Station

The Fanvil i505 Android Indoor Station is a 7-inch touch screen indoor station, boasting a sleek design and user-friendly interface. Powered by Android 9.0, it smoothly integrates with third-party applications.

Fanvil i505 Android Indoor Station Key Features:

ī¿½ 7-inch colour capacitive touch screen provides a more convenient user experience

- آذِا½ Android 9.0 system ensures stable operation, meeting the customisation needs of industry applications and secondary development
- าั¿½ Built-in 2W speaker and AEC algorithm, it achieves high-quality two-way hands-free calling
- ī¿½ Check real-time video of third-party IP cameras and door phone to ensure security
- � Rich interfaces facilitate the integration of various sensors, enabling comprehensive home security monitoring
- � Powered by PoE or external source

Equipped with multiple expansion interfaces, it effortlessly links with security devices, enabling functionalities such as two-way intercom, remote door opening, and alarms. Tailored for use in residential communities, villas, office buildings, and similar settings, it enhances safety and convenience, delivering a seamless and secure living experience.

Fanvil i505 Android Indoor Station Technical Specifications Panel type

ï¿⅓ Community

تىٰ½ Hotel

7ز½ Villa

Screen

آذِيً 7-inch color capacitive touch screen 1024×600

Body

ABS

Speaker

%¿½ 2W يُزَّا

Interface

� 8×Alarm input

� 1×Short circuit output

ï¿1/2 1×Doorbell input

ï¿1/2 1×RS485 (Reserved)

Network

ï¿1/2 10/100 Mbps adaptive

Power Supply



Fanvil i505 Android Indoor Station

� DC 12V / 1A � PoE 802.3af

Power Consumption

� PoE: 2.83~7.64W � Adapter: 2.46~6.51W

Working Temperature

� -10℃~50℃

Storage Temperature

� -40℃~80℃

Working Humidity

� 10%~90%

Size (LWH)

ïز½ 177.38x113.99x22.5mm

Installation

آز½ Wall-mounted

Functional Capabilities

آزٰ 2 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

Audio

าั¿1/2 Narrowband audio codec: G.711A/U, G.729AB, iLBC

 $\ddot{i}\dot{\epsilon}^{1/2}$ Broadband audio codec: G.722, OPUS

آذًا Full-duplex hands-free calling, supports Acoustic Echo Cancellation (AEC)

Video

تز½ Hardware video decoding: H.264, H.265 (Optional)

ї¿½ Video call resolution: QVGA / CIF / VGA / 4CIF / 720P / 1080P

DTMF

ï¿1/2 In-band, out-of-band DTMF (RFC2833), SIP Info

Do Not Disturb (DND)

� Supported, and the time can be user-defined

Additionally

า๊¿½ Supports viewing video from third-party IP cameras



Fanvil i505 Android Indoor Station

- � Supports customising incoming call ringtones
- ï¿⅓ Supports remote door unlocking
- $\ddot{\imath}_{\dot{c}}$ Supports sending/receiving messages
- � Supports the installation of third-party app

Please Enquire