

## Yealink A40 All-in- One Andriod Video Bar for Small to Medium Rooms with CTP25



Product Name: Yealink A40 All-in- One Andriod Video Bar for Small to Medium Rooms with CTP25

Manufacturer: Yealink

Model Number: A40-031

Yealink A40 All-in- One Andriod Video Bar for Small to Medium Rooms with CTP25

The Yealink A40 is an all-in-one video collaboration bar tailored for small-to-medium-sized meeting rooms. Featuring dual 48MP lenses, it captures high-resolution images for clear, detailed visuals. The A40 also includes integrated stereo speakers and an 8x MEMS microphone array, with support for two optional expansion microphones to boost audio pickup. Its intelligent noise reduction technology enhances the audio experience by minimizing background noise for clearer conversations.

Yealink A40 Key Features:

- Ultra HD picture quality
- High-quality audio pickup experience
- Compatible with Microsoft's MDEP
- Multi-Platform Flexibility
- Simple deployment
- Remote device management

Supporting Android 13, the Yealink MeetingBar A40 is future-ready, allowing users to access the latest features and updates. It integrates with Microsoft's MDEP for improved security and streamlined deployment, creating a more secure and efficient setup. The device also connects directly to the Yealink CTP25 control panel, providing a convenient, fast login process that enhances user experience and reduces setup time.

Yealink A40 Technical Specifications  
Specifications

• Operating System: Android 13

Camera

- Maximum pixels: 2 x 48MP
- Number of preset positions: 9
- Electronic gimbal
- Field of view (DFOV): 120°, VFOV: 54°, HFOV: 110°
- Depth of field: 1-5 meters
- Digital zoom: 6x
- Maximum resolution: 4K
- Frame rate: 60FPS
- Video output resolution: 4K60fps, 1080P60fps
- Effective focal length: 4.2 mm
- Aperture: F/2.2-F/2.4
- Supports wide dynamic range and 10-bit high dynamic range imaging
- Auto exposure
- White balance options: ATW/auto/manual
- Shutter speed: 10ms-33ms
- Minimum illumination: 0.5 lux (daytime), 0.1 lux (nighttime)
- Signal-to-noise ratio: >63 dB
- Privacy cover: Electric lens cap
- Lens calibration

## Yealink A40 All-in- One Andriod Video Bar for Small to Medium Rooms with CTP25

ï¿½ Intelligence Features: IntelliFocus, Auto Framing, Speaker Tracking, People Counting, Picture in Picture, Multi-focus Framing, Smart Gallery (Zoom only)

ï¿½ Number of cameras: 2

### Speaker

ï¿½ Built-in speakers: 2 x 10W

ï¿½ Maximum sound pressure level: 112dB SPL 10W@0.1m

ï¿½ Frequency response: 100-16kHz

ï¿½ Sensitivity: 86dB SPL @ 1W @ 0.5 meter

ï¿½ Sampling rate: 48kHz

ï¿½ Sound emission angle: Forward-facing

ï¿½ Total Harmonic Distortion (THD): <5% at 10W, 1kHz

ï¿½ Rated impedance: 4 ohms

ï¿½ Maximum power: 12W

ï¿½ Rated power: 10W

### Microphone

ï¿½ Built-in 8 MEMS microphone array

ï¿½ Pickup distance: 6 meters, high-quality pickup at 4 meters

ï¿½ Signal-to-noise ratio: 72dB

ï¿½ Maximum sound pressure level: 130dB SPL (whole device), 100dB SPL (individual microphone)

ï¿½ Dynamic range: 28-100dB SPL

ï¿½ Sensitivity: -38dBV/pa

ï¿½ Frequency response: 100-20kHz

ï¿½ Sampling rate: 48kHz, 32-bit depth

### Resolution

ï¿½ Portrait resolution: up to 4K30fps

ï¿½ Bandwidth requirement: 10Mbps or more

### Content Sharing

ï¿½ General Mode: Up to 4K15

ï¿½ Teams: 1080p in meeting, 4K local sharing

ï¿½ Zoom: 1080p

### Communication Standard Protocol

ï¿½ SIP/H.323 in General Mode

### Network Protocol

ï¿½ Wi-Fi 6: 2.4G & 5G dual-band, 802.11a/b/g/n/ac/ax with 2x2 MIMO

ï¿½ Bluetooth 5.0

ï¿½ TCP/IP (IPv4/IPv6), DHCP/static IP

ï¿½ HTTPS secure web access

### Configuration Management

## Yealink A40 All-in- One Andriod Video Bar for Small to Medium Rooms with CTP25

- Automatic configuration via web page/display/AutoP
- Firmware upgrade, factory reset
- Configuration import/export
- System log export

### Device Management

- Yealink HTTPS Web Portal, Yealink Device Management Platform, Yealink Management Cloud Service
- Microsoft Device Management Platform (Teams Admin Center/Intune)
- Zoom Device Management

### Installation

- Wall mount, TV-Clip Mount, or place on desktop

### Ports

- 1x USB2.0 USB-A port
- 1x USB-C port
- 1x Ethernet port
- 1x Yealink VCH port (RJ-45)
- 1x 3.5mm Line-in & Line-out port
- 1x Power port
- 1x Security lock slot
- 1x Reset slot
- 2x HDMI-out

### Package

- Contents: MeetingBar A40, HDMI cable x2, Network cable x1, TV-Clip Mount x1, Wall Mount x1
- Optional Packages: A40-010 (A40+VCR11), A40-031 (A40+CTP25)

### Environmental Factor

- Operating humidity: 10 - 95%
- Operating temperature: 0 - 40°C

### Dimensions and Weight (W × D × H)

- MeetingBar A40: 650 × 62 × 80 mm
- N.W/CTN: 5.540 kg

**Price: £1,525.00**