



Product Name: Snom HD1 Hospitality Phone (HD1) Manufacturer: Snom Model Number: HD1

Snom HD1 Hospitality Phone

The Snom HD1 is an additional cordless DECT handset designed to expand the capabilities of the Snom HD101 hospitality phone system. It allows for up to three additional handsets to be connected to a single HD101 base, enabling communication across multiple rooms or areas within a hospitality environment. In addition to their own charging cradle, all handsets have the most important features for the comfort of your guest: hands-free calling, muting and call hold are integrated. It also has an antibacterial housing to protect against germs and is easy to clean. The large visual display draws attention to calls and waiting messages. The handsets can be individually labelled on the handsets.

Snom HD1 Key Features

i¿½ Antibacterial housing
i¿½ Additional Cordless DECT handset
i¿½ Color: gunmetal black
i¿½ Large LED call indicator
i¿½ Backlit Keys
i¿½ Hearing-aid compatible (HAC)

Snom HD1 Technical Specifications Basics

ï¿1/2 Product Information

i¿1/2 Cordless DECT handset|charging cradle|PN 00007002

ï¿1/2 Anti-bacterial housing

ï¿1/2 Colour: Gunmetal Black

ï¿1/2 Sturdy, solid construction

ï¿1/2 Ultra small footprint and compact design

ï¿1/2 Placement: Indoor, Desktop, Nightstand, Wall Mounting

Dimensions and Weight

ï¿¹/₂ Dimensions (H x W x D, Approx.)

ï¿1/2 Handset: 213 mm × 49 mm × 42 mm

ï¿1/2 Charging cradle: 71 mm × 96 mm × 108 mm

ï¿1/2 Handset (on the charging cradle, desk mounted): 71 mm × 115 mm × 214 mm

ï¿1/2 Weight (Approx.)

ï¿1/2 Handset: 178 g

ï¿1/2 Charging cradle: 285 g

ï¿1/2 Handset (on the charging cradle, desk mounted): 469 g



Indicators and Keys

- ï¿1/2 6 LED indicators
- ï¿1/2 Charging cradle
- ï¿1/2 Charging indication: 1 red LED

ï¿1∕₂ Handset

ï¿1/2 Flash/Talk key indication: 1 red LED

ï¿1/2 Mute status indication: 1 red LED

ï¿1/2 Speakerphone mode: 1 red LED

ï¿1/2 Hold status indication: 1 red LED

i¿1/2 Low battery indication | Charging indication: 1 red LED

iزئ 12 keys (standard ITU telephone keypad), backlit iزئ 4 dedicated audio keys

i¿½ SPEAKER ⇒ Speakerphone mode (with red LED) i¿½ MUTE ⇒ Mute (with red LED) i¿½ +VOLUME- ⇒ Volume + / - (rocker)

ï¿1/2 2 programmable function keys

ï¿1/2 Speed dialling

ï¿1/2 5 dedicated function keys

i¿¹/₂ TALK/FLASH ⇒ Offhook (with red LED) i¿¹/₂ EMERGENCY [➕] ⇒ Emergency i¿¹/₂ OFF ⇒ Onhook / Cancel i¿¹/₂ HOLD ⇒ Hold (with red LED) i¿¹/₂ MESSAGES ⇒ Message

Audio Devices and Features

ï¿1/2 Microphone ï¿1/2 Handset earpiece

 $\ddot{\imath}_{{\ensuremath{\mathcal{C}}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{L}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{L}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{L}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{L}}{\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}{\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensuremath{\mathcal{I}}\ensuremath{\mathcal{I}}}\ensurema$

ï¿1∕2 Casing speaker

ï¿1/2 Speakerphone mode (via dedicated function key)



Interfaces and Connections

ï¿1/2 Power Options

� Handset: Battery (CORUN) AAA-NiMH 2.4 V, 550 mAh, preinstalled, removable, rechargeable, up to 7 h talk time, up to 5 days standby time, up to 16 h charging time � Charging cradle: Power adapter (VT-PLII) 100 - 240 V AC, 50/60 Hz, 150 mA|6 V DC, 450 mA, 2.7 W

ï¿1∕2 Wired Interfaces

ï¿1/2 Charging cradle: coaxial power connector (socket)

ï¿1/2 Wireless interfaces

� DECT

DECT technology and features

ï¿1/2 Standard: DECT

 $\ddot{\imath}_{2}\dot{\prime}_{2}$ Authentication/encryption of base and handset $\ddot{\imath}_{2}\dot{\prime}_{2}$ Wideband audio

ï¿1/2 Frequency band

� EU & UK & AU: 1,881.792 - 1,897.344 MHz

 \ddot{i}_{2} Easy registration to compatible base stations (HD101)

Call features

ï¿1/2 Speed dialling via function keys

- ï¿1/2 Mute microphone (via dedicated function key)
- ï¿1/2 Hold (via dedicated function key)
- ï¿1∕₂ Multicast paging
- \ddot{i}_{2} Quick call answer (by simple pick-up from the base/charger)

Environmental conditions

� Operating ambient temperature: 5 °C - 45 °C � Humidity (non-condensing): 5 % - 95 %

Package Contents



ï¿1∕2 Hardware

- ï¿1⁄2 DECT handset HD1
- ï¿1∕2 Battery: preinstalled
- ï¿1/2 Handset cord: 330 mm
- ï¿1/2 Charging cradle
- ï¿1∕2 Power adapter

ï¿1/2 Documentation

ï¿1/2 Quick Installation Guide (QIG)

Snom Accessories and Compatible Devices

� Guest room phone: HD101 (PN 00007001) � Power adapter: Charging cradle HD1 PSU

ī¿½ EU: PN 00004683 ī¿½ UK: PN 00004684 ī¿½ AU: PN 00004685

ï¿1/2 Battery HD1 (PN 00004509)

Please Enquire