

Sangoma NetBorder Express Gateway NBE240A



Product Name: Sangoma NetBorder Express Gateway NBE240A

Manufacturer: -

Model Number: NBE240A

Please Note: This product is no longer available. For more products please view the Sangoma product portfolio.

240 Ports, Software Only - A108D Hardware Required

Introducing the industry's first affordable TDM to SIP Gateway on a card.

Sangoma's NetBorder Express portfolio is a complete SIP-compliant VoIP Media Gateway solution, delivering cost effective solutions for developers, system integrators, and OEMs in a convenient PCI or PCI Express form-factor.

Empowered by Sangoma's NetBorder Express Software, NetBorder Express TDM to SIP Gateway Cards include G.168 Telco-Grade Echo Cancellation with 128 ms echo tails without call capacity reduction to provide optimum operating conditions for applications, such as Speech Recognition IVRs and International Toll Bypass. NetBorder Express cards also feature Sangoma's award-winning field upgradeable crashproof firmware design. NetBorder Express communicates with applications such as IP-PBXs, Speech Enabled IVRs, Conferencing Servers, Contact Center or Trunking Gateways directly with the ubiquitous SIP control protocol to reduce deployment time, complexity and cost for next generation network application deployments. Available for analog FXO and T1/E1 digital interfaces, NetBorder Express Gateway Cards are an excellent value for installations ranging anywhere from 4 to 240 simultaneous calls. For larger systems, several gateway cards can be combined in the same server to support up to 960 simultaneous calls. A simple ordering process, coupled with Sangoma's installation and basic configuration support, plus a lifetime hardware warranty make NetBorder Express the perfect gateway building block for even the smallest SMB on a limited budget. A flexible upgrade path to the full NetBorder Software Suite also translates into unparalleled price performance for the largest enterprise or contact center customer. Technical Specifications Hardware

½ Available in 4, 8, 12 ports of analog FXO, from 1 to 8 ports of T1 or E1.

½ Choice of PCI with Autosense Compatibility for 5 V and 3.3 V busses or PCIe Interface with single lane bus.

½ Fully compatible with all commercially available motherboards—PCI standard interrupt sharing without manual tuning.

½ G.168—2002 Echo Cancellation in hardware included. Supports 1024 taps/128 ms tail per channel on all channel densities with DTMF decoding and tone recognition, voice quality enhancement, acoustic echo control, and adaptive noise reduction.

½ Optimized per channel DMA streams and hardware-level HDLC handling unload the host CPU.

½ 32-bit bus master DMA data exchanges across PCI interface at 132 Mbytes/sec for minimum host processor intervention.

½ Ring buffer DMA handling for minimum host intervention and guaranteed data integrity on high volume systems.

½ Dimensions: 2U Form factor: 120 mm x 55 mm for use in restricted chassis.

½ Includes premium quality RJ45 cables and short 2U mounting clips for installation in 2U rack-mount servers.

½ Power: 800 mA peak, operational 300 mA max at +3.3 V or 5 V.

½ Temperature range: 0—50°C.

Firmware Downloadable, crash-proof (Back-up ROM) FPGA programming with multiple operating modes. Add new firmware features when they become available. Software

Sangoma NetBorder Express Gateway NBE240A

• Capacity from 4 to 240 channels of simultaneous calls on a single card. Up to 960 per system.

• DTMF over RTP per RFC 2833. Custom tone detection and generation.

• RTP/RTCP per RFC 3550/3551.

• SIP Control Protocol per RFC 3261.

• PSTN protocol termination per analog FXO or digital ISDN PRI (including EuroISDN, NI2, DMS, 5ESS).

• Open Protocol Translation and XML based routing rules.

Operating Systems • Windows® XP and Microsoft Server 2003 (32-bit versions).

Management and Configuration • Web Server, Web Services API, and configuration files for easy integration into OEM applications.

T1/E1 Status Alarms

• RED: Telco Red Alarm Condition.

• OOF: Out of Frame.

• LOS: Receive Loss of Signal.

• AIS: Alarm Indication Signal.

• RAI: Remote Alarm Indication (Yellow Alarm).

Diagnostic Tools WANPIPEMON, System logs. Certification FCC Part 15 Class A, FCC Part 68, CISPR 22, EN 55022, Class A, CISPR 24, AFIC-2016, IEC 60950. Technical certifications in Russia, Malaysia, and Australia. Warranty Lifetime parts and labor on hardware. PLUS a 30-day "no questions asked" return policy. Production Quality ISO 9002

Please Enquire