

Yealink T28P IP Phone (SIP-T28P)



Product Name: Yealink T28P IP Phone (SIP-T28P)

Manufacturer: -

Model Number: SIP-T28P

Yealink T28P IP Phone (SIP-T28P)

Please Note: The Yealink T28P has been discontinued. For an alternative, we recommend the Yealink T29G.

The Yealink T28P is a top of the range business VoIP phone, featuring high quality telephony features including a 320 x 160 graphic LCD screen with 4-level grayscales, 6 VoIP accounts which are Broadsoft / Avaya/ Asterisk validated, and the TI TITAN chipset.

Yealink SIP-T28P Features

- 6 SIP Accounts
- 320x160 White Backlit LCD Display
- 4 Level Grayscales
- 16 Programmable Keys
- Logo Customisation on Screen
- Expansion Keypad Available
- Power over Ethernet
- 3 Way Conference Calls
- Speakerphone
- MP3 Ringtones and Voicemail.
- Call Hold, Waiting and Transfer.

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.

Yealink T28P Technical Specifications

Phone Features

- 6 VoIP accounts, Hotline, Emergency call
- Call hold, Call waiting, Call forward, Call return
- Call transfer (blind/semi-attended/attended)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Message Waiting Indication (MWI) LED
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Phonebook (300 entries), Black list
- Call history: dialed/received/missed/forwarded
- Menu-driven user interface
- Localized language and input method
- Soft keys programmable
- Supports up to 6 expansion modules(EXP38 and EXP39)
- Supports Wireless Headset Adapter (EHS36)

Advanced Features

- XML phonebook search/import
- LDAP phonebook

Yealink T28P IP Phone (SIP-T28P)

- XML Browser, Hot-desking
- PUSH XML
- Action URL & Active URI

IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call park, Call pickup
- Call recording, Call completion
- Group listening, Group pickup
- Anonymous call, Anonymous call rejection
- Network conference
- Distinctive ringtone
- Dial Plan, Dial-now

Codecs and Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711µ/A, G.723.1
- G.726, G.729AB
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex speakerphone with AEC

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- IPV6
- DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- Bridge/router mode for PC port
- TFTP/DHCP/PPPoE client
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server
- Logout

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- Auto-provision with PnP
- SNMP V1/2 optional, TR069 optional
- Configuration: browser/phone/auto-provision
- Factory configuration customized
- Trace package and system log export

Security

- Open VPN, 802.1x, VLAN QoS (802.1pq), LLDP
- Transport Layer Security (TLS)

Yealink T28P IP Phone (SIP-T28P)

- ½ HTTPS (server/client), SRTP (RFC3711)
- ½ Digest authentication using MD5/MD5-sess
- ½ Secure configuration file via AES encryption
- ½ Phone lock for personal privacy protection
- ½ Admin/VAR/User 3-level configuration mode

Connectivity

Physical Features

- ½ TI TITAN chipset
- ½ 320 x 160 graphic LCD with 4-level grayscales
- ½ 48 keys including 16 programmable keys
- ½ 1 x RJ9 (4P4C) handset port
- ½ 1 x RJ9 (4P4C) headset port
- ½ 2 x RJ45 10/100M Ethernet ports
- ½ 1 x RJ12 (6P6C) EXT port
- ½ Power adapter: AC 100~240V input and DC 5V/1.2A output (Optional)
- ½ Power over Ethernet (IEEE 802.3af)
- ½ Power consumption: 1.6-2.6W
- ½ Net weight: 1.05KG
- ½ Dimension: 273 x 204 x 42mm
- ½ Operating humidity: 10~95%
- ½ Storage temperature: up to 60°C

Yealink T28P Certifications

Please Enquire

Options available for Yealink T28P IP Phone (SIP-T28P) :

Power Supply Required?

[UK PSU required \(+£3.99\)](#), [EU PSU required \(+£3.99\)](#), [None - Using PoE.](#)

RPS Extension ID

[TEXT.](#)

RPS Extension Password

[TEXT.](#)

RPS Display Name

[TEXT.](#)

RPS PBX URL

[TEXT.](#)

RPS NAT Enabled

[TEXT.](#)

RPS Outbound Proxy

[TEXT.](#)

Yealink T28P IP Phone (SIP-T28P)

RPS SIP Port

TEXT.

RPS Enable Outbound Proxy

RPS Own Server URL

RPS Own Server Name

Yealink EXP38 IP Phone Expansion Module

Required (+£67.00), Not Required.

Yealink EXP39 IP Phone Expansion Module

Required (+£87.75), Not Required.