

## Positron Telecom V-114 Asterisk PCI Card



Product Name: Positron Telecom V-114 Asterisk PCI Card

Manufacturer: -

Model Number: V-114

Availability: In Stock Positron Telecom V-114 Asterisk PCI Card with H/W E-C; 4 FXO + 1 FXS + Ethernet

The V-114 PCI card is a leap forward in the telecommunications market. It is the first card of its kind to offer the functionality of Asterisk® PBX on a card with integrated telephony ports, hardware-based echo cancellation and Ethernet interface. By integrating the Linux, Asterisk, Echo Canceller, Ethernet (for PCI and LAN), Telephone ports (FXS) and Gateway functionality (FXO) we have created the first standalone solution that can be installed in any PC and by interfacing Ethernet to the PCI bus we have also made the solution any Operating System – no special drivers required. Highlights

- ½ Installs simply and quickly as an Ethernet adapter
- ½ Installs in ANY Operating System
- ½ Allows any SIP based application to speak directly to the card – no API integration
- ½ No additional hardware setup required – unlike other card solutions
- ½ Provides the functionality of PBX
- ½ Features & Benefits and Gateway in one solution

### Features and Benefits

- ½ Integrated PBX
- ½ Simplifies Installation, configuration
- ½ Hardware Echo Cancellation
- ½ Installs as an Ethernet Device
- ½ Can be plugged into any Operating System
- ½ Integrated FXO, FXS and Ethernet
- ½ Gives greater flexibility in functionality and requires no additional driver installation
- ½ Cross Board Switching
- ½ No drivers required

### Technical Specification - Hardware Specification V114-Analog

- ½ Single Compact Flash port
- ½ 4 Foreign Exchange Office (FXO) ports for connection to the telephone network
- ½ Single Foreign Exchange Station (FXS) port for connecting a phone or fax machine
- ½ Hardware based G.168 echo cancellation chip up to 128ms tail length
- ½ PCI 2.2 compliant Ethernet interface
- ½ 10/100Mbps auto MDIX Ethernet port
- ½ Per channel fax / modem G.164 pr G.165 2100Hz phase reversal tone disable
- ½ ITU-T G.165, G.168 (2000) and (2002) compliant

### Interfaces

- ½ Telephone Interface: Four FXO, RJ-12, One FXS – RJ-11
- ½ Network Interface: 10/100 Mbps RJ-45, PCI
- ½ LED indicators: Power, Fault, Network, Link speed

### Environmental

- ½ Operating Range: 0&deg;C to 40&deg;C
- ½ Storage: -20&deg;C to 85&deg;C

## Positron Telecom V-114 Asterisk PCI Card

• Humidity: 10% to 80%

### Dimensions

• H: 107 mm (4.2 inches)

• D: 312 mm (12.283 inches)

### Warranty

• 2 years

### Codec Support

• G.711 ulaw & alaw

• G.729 a/b

• GSM

• Speex

### Standards & Approvals

• FCC Part 68

• CE Mark

• EMC: FCC Part 15

• PCI 2.1 complaint

Ordering information • Product Code: 70-00005-01

**Price: £369.00**

---