Citel C4110 SIP + IAX VoIP Phone

Product Name: Citel C4110 SIP + IAX VoIP Phone

Manufacturer: -

Model Number: C4110

Citel C4110 SIP + IAX VoIP Phone
Citel C4110 SIP + IAX VoIP Phone is a 3 Line desktop VoIP phone that delivers high voice quality and is packed with features. It supports both IAX2 and SIP protocols.
The Citel C4110 can easily be configured via a web browser, and also supports convenience auto-provisioning via TFTP server. The C4110 features 8 distinctive ring tones, volume and ringer level control, and voicemail retrieval via keypad or programmable keys. With an integrated 2 port 10/100 MBPs switch, 802.3af Power Over Ethernet, RJ9 headset jack and VLAN/DHCP support. This phone is PoE compatible; however power supply units are also available.

ï¿½ Two lines / call appearances with LEDs
ï¿½ Conference calling (with or without server)
ï¿½ Call transfer (blind or consultative)
ï¿½ Call hold, call waiting, and call forwarding
ï¿½ Caller ID and Call-waiting caller ID
ï¿½ Do not disturb
ï¿½ Number note pad
ï¿½ Paging
ï¿½ Auto answer
ï¿½ Configurable dial plan
ï¿½ 500 entry phone book
ï¿½ Keypad dialing
ï¿½ Speed dial from phone book and call log
ï¿½ 100 number redial list
ï¿½ Menu layout for easy navigation via softkey
ï¿½ Missed / outgoing / incoming call logs, 100entries each voicemail retrieval via keypad or programmable keys
ï¿½ 8 distinctive ring tone
ï¿½ Volume and Ringer level control
ï¿½ 4 or 12 (with expansion module) programmable keys for speed dial or feature access.
ï¿½ Spanish, French, Chinese and English language compatible.

Citel C4110 SIP + IAX VoIP Phone Technical Specification
Protocols Supported

ï¿½ SIP (RFC3261, RF3262)
ï¿½ IAX2
ï¿½ SDP (RFC2327)
ï¿½ (SIP) Subscribe / Notify (RFC3265)
ï¿½ (SIP) Offer / Answer Model (RFC3264)
ï¿½ (SIP) Refer Method (RFC3515)
ï¿½ DTMF transport (RFC2833)
ï¿½ SIP INFO and in-band DTMF transport
ï¿½ RTP / RTCP (RFC3550, 3551)
(SIP) DNS SRV (RFC2781)

Audio / Codec:

ï¿½ G.711 A law and G.711 U law 64K
ï¿½ G.729

Citel C4110 SIP + IAX VoIP Phone

ï¿½ G.723.1
ï¿½ DTMF tone Generation
ï¿½ Acoustic echo cancellation
ï¿½ Built-in audio mixer

Voice Protocols

ï¿½ SIP (per IETF-SIP-RFC3261)
ï¿½ IAX2
ï¿½ RTP
ï¿½ G.711 u-law
ï¿½ G.711 A-law
ï¿½ G.729 A/B
ï¿½ Silence Suppression
ï¿½ Comfort Noise Generation
ï¿½ G.168 Echo Cancellation

Price: £75.00

Options available for Citel C4110 SIP + IAX VoIP Phone :

Power Supply Required?
Power Supply For C4110 (+£10.00),   - Not Required -.