

Valcom VIP-120-IC One Way SIP Ceiling Speaker

	1	1	b.	1
1		~		1
	1		y	/

Product Name: Valcom VIP-120-IC One Way SIP Ceiling Speaker Manufacturer: -Model Number: VIP-120-IC

Availability: In Stock

Valcom VIP-120-IC One Way SIP Ceiling Speaker

The VIP-120-IC One-Way IP Ceiling Speaker enables voice access to a single zone of one-way paging over an IP-based LAN/WAN. This allows a page zone extension anywhere on the network. The speaker level is electrically adjusted during set up. The enclosure is made of steel with a durable white powder coated finish. Power is provided to the VIP-120 via a Power over an Ethernet switch meeting the 802.3af specification. Valcom VIP-120-IC SIP Celing Speaker Features

- i¿½ Exceptional Voice & amp; Music Reproduction
- ï¿1/2 Contains Its Own Built-In Amplifier
- ï¿1/2 White Epoxy Finish
- ï¿1/2 Volume Control

Valcom VIP-120-IC SIP Celing Speaker Core Features

- i¿1/2 SIP And Multicast Enabled
- ï¿¹/₂ Easy To Install via RJ-45
- ï¿1/2 PoE (802.3af)
- ï¿1/2 Live, Recorded Or Scheduled Messages
- تزائد Easily Connect Loudspeaker System To Existing Computer Networks
- ïزائ Compatible With Cisco, Nortel, Avaya And Most IP Telephone Systems
- ï¿1/2 One-Way Paging
- ï¿1/2 Web Interface For Control And Setup
- ï¿¹/₂ Can Operate Over Secure Networks
- ï¿¹∕₂ Paging Prioritization
- ï¿1/2 Background Music
- ï¿¹/₂ Web-based Firmware Upgradeable
- ï¿1⁄₂ High Efficiency
- ï¿1/2 Line Out Supports Amplified Speakers
- ï¿1/2 Wireless Option
- ï¿1/2 Synchronized Clock Option
- ï¿1/2 Full Supervision
- ï¿1∕₂ Wireless Option
- ï¿1/2 Test / Setup Tones
- ï¿1/2 Software Developer Kit Available
- i¿1/2 Compatible With Text/Audio To IP Telephones
- ï¿1/2 Supports Syn-Apps, Checkmate, PagePro IP
- � DHCP

Valcom VIP-120-IC SIP Celing Speaker Specifications Power

ï¿1/2 External: 24 VDC @ 325 ma

ï¿1/2 POE: 802.3af, class 3

Networking

- ï¿¹/₂ 10/100 Mbps Ethernet port
- تزائد Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup.
- ï¿1/2 Time and date synchronization using SNTP



Valcom VIP-120-IC One Way SIP Ceiling Speaker

Protocols

- ï¿1⁄2 IETF SIP (RFC3261)
- ï¿1/2 IETF IGMP version 3 (RFC3376)
- ï¿1⁄₂ IETF RTP (RFC1889)
- ï¿1⁄2 IETF RFC2833
- ï¿1/2 Digest Authentication
- ï¿1/2 Dimensions and Weight
- ï¿1/2 Dimensions: 12.88" H x 12.88" W x 4" D (32.7 cm x 32.7 cm x 10.2 cm)
- � Weight: 2.7 lbs (1.22 kg)

Price: £574.40