

Valcom VIP-172L-VRSS IP Intercom



Product Name: Valcom VIP-172L-VRSS IP Intercom

Manufacturer: -

Model Number: VIP-172L-VRSS

Availability: In Stock

Valcom VIP-172L-VRSS IP Intercom - Vandal resistant 11 Gauge Stainless Steel

The VIP-172L series of IP Handsfree Talkback intercom with longline extender and dial code operated relay are the perfect solution to implementing Door Phone or similar functions with modern IP telephone systems. In a door answer application, a visitor pressing the "Call" button on the doorplate initiates a call to any SIP telephone, Valcom intercom station or to a Valcom IP gateway. When the called party answers, handsfree talkback communication is enabled. The called party may dial a code to activate a relay in the IP DoorPhone to unlock the door. When the called party terminates the call, the session is terminated automatically. The called party may be anywhere, across the street or across the world.. When used in a Command application, any location will automatically call the Command location. The Command location can call any station directly. The Command location can call any groups or can do an all call page using a single optional Valcom multicast Gateway. FEATURES:

- SIP DoorPhone w/ door/gate relay
- Power over Ethernet (PoE) compatible
- Use with Cisco, Nortel, Avaya, and most modern IP Telephone systems
- Call button calls any SIP address or any Valcom Gateway
- Automatic Talkback VOX operation (no Push To Talk button needed)
- Includes long line extender – up to 300 meters between network interface and door speaker
- Easy, RJ45 plug in connection
- Stainless Steel, Brass and Vandal-Resistant (11 Gauge Steel)
- Companion to IP CCTV Cameras
- SIP or Multicast communications
- All Call 1000's of units with Valcom Gateway
- LED Status Indicator
- Weather and Tamper Resistant
- Compatible with secure networks
- Supervision with Alert Functions
- DHCP addressable
- High Survivability –No Server Needed

Valcom VIP-172L SIP Intercom Specifications SPEAKER 2 inch SWITCH Single Pole Momentary Contact MOUNTING:

- VIP-172L Mounts in a double gang (4" x 4") electrical box
- VIP-173L Mounts in a 2-gang (4" x 4") electrical box with one-way screws

RELAY OUTPUT

- (1) Form C contact
- Visual LED Status
- Programmable activation period

POWER

- Extend: 24 VDC @ 325 ma
- POE: 802.3af, class 3

NETWORKING

Valcom VIP-172L-VRSS IP Intercom

- 10/100 Mbps Ethernet port
- Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup.
- Time and date synchronization using SNTP

PROTOCOLS

- IETF SIP (RFC3261)
- IETF IGMP version 3 (RFC3376)
- IETF RTP (RFC1889)
- IETF RFC2833
- Digest Authentication

DIMENSIONS AND WEIGHT:

- 4.5" H x 4.5" W x 1.3" D (11.43 cm x 11.43 cm x 3.3 cm)
- Weight: .55 lb (.25 kg)
- Shipping Weight: 1.6 lb. (.72kg)

Price: £638.40
