

**CyberData V2 VoIP Loudspeaker Amplifier - Wireless (011096)**

Product Name: CyberData V2 VoIP Loudspeaker Amplifier - Wireless (011096)

Manufacturer: -

Model Number: 011096

Please Note: The CyberData V2 VoIP Loudspeaker Amplifier has been discontinued. For an alternative, please see our range of CyberData Speakers / Loudspeakers Amplifiers.

Note: The loudspeaker Horn is not included. Please order the Loudspeaker Horn separately.  
VoIP V2 Loudspeaker Amplifier, Wireless

Now with up to 25 watts output (802.3at) The new CyberData V2 SIP-enabled VoIP Loudspeaker Amplifier provides an easy method for implementing an IP-based overhead paging system for both new and legacy installations. The CyberData V2 SIP-enabled VoIP Loudspeaker Amplifier replaces CyberData VoIP Loudspeaker Amplifier Wireless (010860) With up to 25 watts of driving power (802.3at), the Amplifier provides direct drive of a standard Horn speaker and supports a line-out connector for connection to an external amplifier. The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the Loudspeaker Amplifier can be configured to listen to multicast address and port number combinations to form paging zones. Ringer Mode The VoIP V2 Loudspeaker Amplifier supports two SIP extensions. One extension can be assigned to a page group for auto answer paging. The second extension can be assigned to a First-to-Answer ring group with IP phones. An audio ring file is activated when the second SIP extension of the ceiling speaker is dialed. If any of the IP phones in the ring group is answered (or if the caller hangs up), the Loudspeaker Amplifier stops ringing. Features

- ½ SIP and Simultaneous Multicast
- ½ Dual-speed ethernet 10/100 Mbps
- ½ Web-based configuration
- ½ PoE 802.3at and 802.3af-enabled
- ½ Line-in for background music
- ½ Line-out connector
- ½ DTMF controlled relay
- ½ Direct 8 Ohm speaker drive
- ½ User-uploadable tones and messages
- ½ Digital and manual volume control
- ½ Second SIP endpoint "Night Ringer"
- ½ Autoprovisioning
- ½ Auto-call voice message from input port sense

#### Loudspeaker Amplifier Specifications

- ½ Ethernet I/F 10/100 Mbps
- ½ Power Input PoE 802.3at or 802.3af
- ½ Operating Temperature -30 to 55 C (-22 to 131 F)
- ½ Protocol SIP RFC 3261
- ½ Payload Types G711
- ½ Regulatory Compliance FCC Class A, CE
- ½ Warranty 2 Years Limited
- ½ Dimensions 14" x 10" x 4"
- ½ Output 802.3af - up to 8 watts
- ½ 802.3at - up to 25 watts
- ½ Lineout: - Output Signal Amplitudes 2.0 VPP maximum - Output Level +2dBm nominal - Total Harmonic Distortion 0.5% maximum - Boxed Weight 6.5 lbs.
- ½ Part Number - Loudspeaker Amplifier, AC 011095 - Loudspeaker Amplifier, Wireless

CyberData V2 VoIP Loudspeaker Amplifier - Wireless (011096)

011096 - Loudspeaker Amplifier, PoE 011097

Installation

**Please Enquire**

---