

Yealink T12P IP Phone (SIP-T12P)



Product Name: Yealink T12P IP Phone (SIP-T12P)

Manufacturer: -

Model Number: SIP-T12P

Please Note: The Yealink T12P has been discontinued. We recommend the Yealink T18 as a good alternative.

Yealink T12P IP Phone (SIP-T12P)

The Yealink T12 is the ideal standard IP Phone for any small business or home user. Equipped with powerful TI TITAN chipset and voice engine, it ensures excellent voice clarity clearly delivered.

Furthermore it is fully interoperable with the majority of IP Telephony platforms available. Combined with sleek design, simplified deployment and application, powerful features and flexibility, it offers an unrivalled cost-effective VoIP solution to meet every-day internet VoIP Services demand. Specification Phone Features

- 2 VoIP accounts, hotline, emergency call
- Call waiting, call transfer, call forward
- Hold, mute, flash, auto-answer, redial
- 3-way conference, DND, speed dial
- XML Phonebook search/import/export
- Black list, call history
- Volume adjustment, ring tone selection
- Tone scheme, System log
- Multi-language (more than 20)

IP PBX System Integration

- Dial plan, dial-now
- SMS, Voicemail, MWI
- Intercom
- Call park, call pickup
- Distinctive ringtone

Codecs and Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711, G.723.1, G.726, G.729AB
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex speakerphone with AEC

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP/PPPoE
- TFTP/DHCP/PPPoE client
- Telnet/HTTP/HTTPS server

DNS client

Yealink T12P IP Phone (SIP-T12P)

• NAT/DHCP server

Management

- FTP/TFTP/HTTP/PnP auto-provision
- Configuration: browser/phone/auto-provision
- Direct IP call without SIP proxy
- Dial number via SIP server
- Dial URL via SIP server

Security

- HTTPS (server/client)
- SRTP (RFC3711)
- Transport Layer Security (TLS)
- VLAN (802.1 pq), QoS
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/user configuration mode

Physical Features

- TI TITAN chipset
- 132x64 graphic LCD
- 24 keys including 4 soft keys
- 1xRJ9 handset port
- 2xRJ45 10/100M Ethernet ports
- Power adapter: AC 100~240V input and DC 5V/1.2A Output (Optional)
- Power over Ethernet (IEEE 802.3af)
- Power consumption: 1.4-2.6W
- Net weight: 0.762kg
- Dimension: 280x215x90mm
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

Package Features

- Qty/CTN: 5PCS
- N.W/CTN: 5.680KG
- G.W/CTN: 6.400KG
- Measurement: 0.0352CMB
- CartonMeas: 470x287x222MM

Please Enquire