

## Sangoma Vega 60G Gateway 2 BRI



Product Name: Sangoma Vega 60G Gateway 2 BRI

Manufacturer: Sangoma

Model Number: VEGA-60G-02BRI

Sangoma Vega 60G Gateway 2 BRI

The Sangoma Vega 60G 2 BRI Media Gateway is designed to simplify the integration of Basic Rate ISDN (BRI) devices to a VoIP network. Each BRI interface can be independently configured as network side or terminal side. The Vega 60G 2 BRI Media Gateway can, therefore, be used for IP PBX connectivity to PSTN and SIP trunking offerings.

Sangoma Vega 60G 2 BRI Gateway Key Features

- 2 BRI Ports

- Flexible Call Routing

- Emergency Backup with Enhanced Network Proxy

- Interoperability with a Wide Range of Legacy & IP Equipment

- Voice, FA, and Modem Support

- Automated Configuration with TR-069

Sangoma Vega 60G 2 BRI - Technical Specifications

VoIP Interfaces

- SIP V1, V2

- Fax support &dash; up to G3 FAX, T.38

- Modem support &dash; up to V.90, G.711

- Audio Codecs: G.711 (a-law/&mu;-law), G.729a (8kbps), G.723.1 (5.3/6.4 kbps), G.726, T.38

Telephony Interfaces

- 2x S/T interfaces presented on RJ-45

- Point to point or point to multipoint

- Each interface configured NT or TE High precision clock optional

LAN Interfaces

- 1x RJ-45 Gigabit Ethernet 1000BaseT / 100BaseTx / 10BaseT, full / half duplex

- PoE option available on some models

- Dual LAN port option available

Telephony Features

- Call waiting

- Call forward &dash; unconditional, busy, no-answer

- Call transfer &dash; blind, consultative 3-way conference

- Do not disturb

- Message waiting indicator &dash; audible, visual

- Music on hold

- Executive barge

- Caller ID presentation & screening

- SIP registration & digest authentication

Operations, Maintenance & Billing

## Sangoma Vega 60G Gateway 2 BRI

- HTTP(S) web server
- RADIUS accounting & login
- Remote firmware upgrade
- Auto configuration upgrade
- SNMP V1, V2 & V3
- Syslog
- TR-069 / TFTP / FTP support
- VT100 & RS232 / Telnet / SSH
- Voice readback of IP parameters

### Routing & Numbering

- Direct Dialing In (DDI)
- SIP registration to multiple proxies
- Dial planner & sophisticated call routing capabilities, standalone or gatekeeper / proxy integration

### Call Quality

- Adaptive jitter removal
- Silence suppression
- Type of Service (ToS)
- Differentiated Services (DiffServ)
- Comfort noise generation
- 802.1p / Q VLAN tagging
- QoS statistics reporting
- Echo cancellation (G.168 up to 128ms tail)

### Security & Encryption

- Media & SRTP
- SIP & TLS
- Management & HTTPS, SSH Telnet
- Configurable user login passwords

### Certification

- EMC (Class B): EN55022, EN55024, FCC Part 15, AS/NZS3548, VCCI
- Safety: EN60950, IEC60950, UL60950, AS/NZS60950

### Environmental

- 0°C; .. 40°C
- 0% .. 90% humidity (non-condensing)

### LED Indicators

- LAN: speed / activity

### Physical Dimensions

- 1U: 200 x 127 x 43mm (WxDxH)
- Weight: .8kgs (1.7lbs)

## Sangoma Vega 60G Gateway 2 BRI

### Power

1/2 Standard product: External 12V 24W AC/DC adapter

**Price: £429.50**

Options available for Sangoma Vega 60G Gateway 2 BRI :

### Peace of Mind Packages

Platinum (+£190.91), Not Required, Gold (+£127.27).