

Grandstream DP710 Additional Handset



Product Name: Grandstream DP710 Additional Handset

Manufacturer: -

Model Number: DP710

Please Note: The Grandstream DP710 Additional Handset has been discontinued. For an alternative, we recommend the Grandstream DP720 DECT Handset

Grandstream DP710 DECT Additional Handset

The Grandstream DP710 is an Additional Handset for the DP715 DECT Base Station. The DP710 offers users an affordable, powerful, high quality and simple to configure VoIP DECT phone, and is designed specifically for both residential users and small business.

Grandstream DP710 Key Features

- DP715 includes the bases station and handset; DP710 includes one handset
- Ring Group/Hunt Group (linear mode, shared line mode, parallel mode) when multiple handsets share the same SIP account
- Range of 300 meters outdoors and 50 meters indoors
- DECT base station allows 5 registered DECT handsets and up to 4 concurrent calls
- 10 hour talk time, 80 hour standby time

Grandstream DP710 Additional Handset Technical Specification

Air Interfaces

• Telephony standards: DECT / GAP Frequency range: 1880 - 1900 MHz (Europe), 1920 - 1930 MHz (US) Number of channels: 120 (Europe), 60 duplex (US) Modulation: GFSK Speech coding: 32 kbit/s Emission power: 10 mW (average power per channel) Range: up to 300 m outdoors, maximum of 50 m in buildings

Handset Display

• 1.7" 102x80 FSTN LCD with color backlight

Audio Interface

• Handsfree speaker

Telephony Features

• Caller ID display or block, call waiting, Flash, blind or attended transfer, forward, hold, do not disturb, 3-way conference

QoS

• Layer 2 (802.1Q VLAN/802.1p), Layer 3 (ToS, DiffServ, MPLS)

IP Transport

Grandstream DP710 Additional Handset

• RTP/RTCP

DTMF Method

• In-audio, RFC2833 and/or SIP Info

IP Signaling

• SIP (RFC 3261)

Multiple SIP accounts per base station

• Up to five (5) distinct SIP accounts per system; Independent SIP account per handset;
Multiple handsets per SIP account

Hunting Group

• Linear mode; Parallel mode; Shared Line mode

Provisioning

• HTTP, HTTPS, TELNET, TFTP, TR-069 (pending), secure and automated provisioning

Security

• Security protection: SIP over TLS and SRTP.

Device Management

• Web interface or secure (AES encrypted) central configuration file for mass deployment

Phonebook(Per Handset)

• 200 numbers (up to 24 digits) with an associated name (up to 16 characters); 10 outgoing call entries; 30 incoming calls entries

Multi-language Input

• English; Latin; Greek; Russian

Polyphonic Ringtones

• 18 different ringer melodies are available to indicate an incoming call (internal intercom or external VoIP)

Price: £14.30

Grandstream DP710 Additional Handset

Options available for Grandstream DP710 Additional Handset :

Compatible Headsets

Not Required, [VXi UC ProSet 21v Headset QD1027 \(+£83.80\)](#), [VXi UC ProSet 10v Headset QD1027 \(+£71.30\)](#),
[VXi CC Pro 4010P DC, Mono \(203503\) \(+£52.90\)](#).