

## Epygi QuadroM26x Hybrid IP PBX



Product Name: Epygi QuadroM26x Hybrid IP PBX

Manufacturer: -

Model Number: QuadroM26x

Epygi QuadroM26x: Small Business Hybrid PBX Solution

The Epygi QuadroM26x offers support for 26 analog devices and up to 80 IP phone extensions. In addition, this system supports SIP lines to connect to an internet service provider and eight FXO lines for a medium-size hybrid office environment. Any user on the system, whether they are on an IP or analog phone, will have access to the advanced VoIP features offered on the QuadroM26x. Even remote users will be able to take advantage of the cost-saving and performance-enhancing features.

The QuadroM26x is designed for offices up to 106 users but can offer performance and features usually only available on much larger enterprise products. These features include Automatic Call Distribution (ACD) for call centers, audio conferencing, call recording and barge-in features. Advanced features are purchasable items, so customers can choose what they pay for instead of being locked into a one-size-fits-all solution. Even though the QuadroM26x is designed for medium-size offices, the new owner can be comfortable knowing they are using an enterprise-grade solution backed by Epygi's support and guaranteed reliability. Epygi QuadroM26x Hybrid IP PBX Benefits

• Hybrid Flexibility

• Easy Migration

• Latest SIP Technology

• Purpose-Built Appliance

Note: Please refer to the Epygi IP PBX Range Detailed Comparison Table for more information.

Technical Specifications

PBX Features

• Call blocking, Forwarding, Hold, Transfer

• Call relay, Call waiting, Caller

• ID Detection

• Voice mail

• Call park, Pickup, Paging, Intercom

• Multi-level auto attendant with Interactive

• Voice Response (IVR) and VoiceXMLv2 support

• Voice mail with SMS notification

• Distinctive ringing

• Speed dialing

• Many extension ringing

• Receptionist

• Call hunting, Hiding Caller ID

• Automated Call back from Auto

• Attendant

• Hold music

• Call statistics

• Do Not Disturb

• Unified messaging

• 3-way conferencing

• Hotline service

• T.38 fax, fax relay and clear channel fax

• Unified Fax Messaging

• Busy auto-redial

• Directory assistance

## Epygi QuadroM26x Hybrid IP PBX

- 1/2 Dial plans (call routing)
- 1/2 Time of day routing
- 1/2 Call Queue
- 1/2 Voice Mail profile
- 1/2 Automatic Call Distribution\*
- 1/2 Call Recording (20 ports) \*
- 1/2 Barge-in \*
- 1/2 Audio (32 ports)/Video (10 ports)
- 1/2 Conference Server \* \*Requires a software license key

### Voice and Video Features

- 1/2 Voice Coding: G.711, G.726 (16, 24, 32, 40 Kbps), G.729A, iLBC (13,33 kbit/s, 15,2 kbit/s); VAD, CNG, G.168 echo cancellation G.722 pass-through point-to-point HD call
- 1/2 Video Coding: H.263 and H.264 pass-through point-to-point video call
- 1/2 VoIP Encryption: SRTP
- 1/2 VoIP Signaling SIP, SIP/TLS DTMF
- 1/2 In band & out of band signaling support.

### VoIP Data and Signaling Protocols

- 1/2 ITU-T G711, G.726, G729 Annex A; IETF RFC 3951- iLBC; ITU-T Q.23, Q.24; Bellcore GR.506, GR.181; ITU-T G.168- 2000, 2002; ETS\_300659\_1,2,3; SIP, SIPS/TLS (RFCs: 2246, 3261, 3263, 3265, 3311, 3323, 3324, 3325, 3428, 3515, 3578, 3581, 3725, 3842, 3856, 3863, 3891, 3892, 4028, 4235) SDP (RFC: 2327, 4568) RTP/SRTP (RFCs: 1889, 1890, 2833, 3389, 3550, 3551, 3555, 3711, 4733, 3952), Fax over IP (ITU-T: T4, T30, T38, V17, V21, V27 ter, V29)

### POTS Signaling

- 1/2 Loop start
- 1/2 FSK and DTMF Caller ID support

### DTMF

- 1/2 In band & out of band signaling support

### Physical interfaces

- 1/2 Premise connections: 2 FXS short-loop FXS ports (RJ-11) 24 FXS short-loop FXS ports (RJ-21) 1 LAN Ethernet 10/100 BASE-T port (RJ-45)
- 1/2 Uplink connections: 8 FXO ports to the Central Office (RJ11) 1 WAN Ethernet 10/100 BASE-T (RJ45)
- 1/2 Audio port connections: Line-in/Line-out (Line-in Signal Level- 0,5 V RMS, Line-out Load Resistance - 600 Ohm to 10K Ohm)

### Phones

- 1/2 IP phones: 16 SIP phones by default 64 additional SIP phones may be added with feature keys All SIP phones can be connected both from LAN or WAN side Plug-and-Play with select IP Phone manufactures

### Auto Attendants and Virtual Extensions

- 1/2 Auto Attendants: Up to 200 standard and custom AA can be registered
- 1/2 Virtual Extensions: Up to 200 Virtual Extensions can be registered\*\* \*\*The total number of

## Epygi QuadroM26x Hybrid IP PBX

extensions used for IP phones, Analog phones, AA and virtual extensions can not exceed 200 extensions.

### System Capacity

- Up to 45 simultaneous VoIP calls with external parties
- Unlimited station to station calling for IP phones
- Unlimited station to station calling for analog phones
- 8 analog PSTN calls with external parties

### External Storage

- Compact Flash

### Management

- Multilingual WEB interface accessible from LAN and WAN (HTTP/HTTPS) Password control
- Remote diagnostics and software upgrade Auto-provisioning
- VoIP Carrier Wizard
- Download/restore configuration
- Legible and editable configuration files
- Auto-configuration of IP phones via TFTP and HTTP
- SNMP Monitoring and Configuration
- Third Party Call Control XML RPC
- Reset button with factory reset option
- Billing Radius Client (RFCs: 2865, 2866)
- Diagnostics/Testing LEDs: Busy, Info, Fault, LAN, WAN, Loop settings Remote testing

### Internet

- STUN/NAT traversal (RFC 3489)
- IPSec VPN with DES, 3DES and AES encryption in tunnel mode (RFCs: 2402, 2406, 2409). Manual and automatic IKE key support
- PPTP VPN
- L2TP VPN
- Firewall security via: Intrusion Detection System NAT (Network Address Translation)
- Policy and service-based filtering
- Stateful inspection firewall
- DHCP server on the LAN side
- DHCP client on the WAN side
- DNS server with forwarding functionality
- SNTP (Simple Network Time Protocol) server/client for computer clock synchronization
- PPPoE connection to the ISP with
- PAP/(MS)CHAP authentication
- IP DIFFSERV for QoS
- Virtual LAN (VLAN/IEEE 802.1Q)
- Mail client to send voice and fax messages as e-mail attachments (.wav and .tif) and system notifications
- DNS (DYNDNS) support with third party
- NAT/Router with port forwarding and port translation.

### Environmental

- Physical Dimensions Rack-mountable devices: Measurements: 19" x 7.56" x 1.77" (48.0 x 19.2 x 4.5 cm)

## Epygi QuadroM26x Hybrid IP PBX

- Weight: 2.47 lbs.(1090 g)
- Conditions 41&deg;F - 104&deg;F (5&deg;C - 40&deg;C) operating temperature
- 41&deg;F - 140&deg;F (5&deg;C - 60&deg;C) storage temperature
- 5% - 90% non-condensing humidity
- Power Supply Input 100 - 240 VAC; 50/60 Hz; 0.5 A
- Regulatory Compliance
- Telecom: TBR12/TBR13; AS/ACIF

**Please Enquire**

---