

# Ubiquiti AirCam Dome H.264 megapixel IP Camera



Product Name: Ubiquiti AirCam Dome H.264 megapixel IP Camera Manufacturer: -Model Number: AirCam-Dome

Please Note: This product has been discontinued. We recommend the Ubiquiti UniFi Video Camera G3 - UVC-G3 as an alternative.

Ubiquiti AirCam Dome IP Camera

The Ubiquiti AirCam Dome IP Camera features a H.264 megapixel camera which combines advanced industrial design, powerful performance with market leading cost-effectiveness. The Ubiquiti AirCam Dome comes complete with Built-in Microphone, Ceiling Mount and has a frame rate of 30 FPS.Ubiquiti AirCam Dome IP Camera Features

i ¿½ Built-in Microphone i ¿½ Ceiling Mount i ¿½ 30 FPS i ¿½ 1MP/HDTV 720p i ¿½ 1.96 mm / F2.0 i ¿½ Powered through Ethernet

Ubiquiti AirCam Dome IP Camera Technical Specifications Camera

� Ports: (1) 10/100 Ethernet, Micro SD Card Slot
� Sensor: Progressive Scan RGB CMOS & frac14;"
� Lens: 4.0mm/F1.5
� Horizontal of View: 47°
� Power: LED Orange
� Link/Active: LED Green
� Buttons: Factory Reset Button
� Maximum Power Consumption: 3.5 Watts

Video

ï¿1/2 Video Compression: H.264/MPEG-4/MJPEG

ï¿<sup>1</sup>/<sub>2</sub> Resolution: 1MP/HDTV 720p

ï¿1/2 Maximum Frame Rate: 30 FPS

ï¿1/2 Image Setting: Brightness, Contrast, Sharpness, Saturation, Mirror, Flip, 50Hz/60Hz

Audio

ïزئ Built-In Microphone: ECM (Omni.); Sensitivity=-42±3dB ; S/N=60dBA

General

ï¿1/2 Processor: ARM-based 32-bit RISC

ï¿1/2 Memory: 128MB DDR2 SDRAM, 8MB Flash

ï¿1/2 Local Storage: Micro SD Card Slot (card not included)

ï¿1/2 Maximum Active Array Size: 1280x800

ï¿1/2 View Angle: 47° (H), 31° (V), 54° (D)

Network



# Ubiquiti AirCam Dome H.264 megapixel IP Camera

� Security: Multiple user access with password protection, Access log � Protocols: IPv4/v6, HTTP, UPnP, DNS, NTP, RTSP, DHCP, TCP, UDP, IGMP, RTCP, ICMP, ARP

#### Power

� Method Passive Power over Ethernet (12-24V) � Power Supply: 24V/0.5A PoE Adapter included

### Physical

� Dimensions: 100 x 94 mm (length x diameter)
� Weight: 179.66 g
� Mounting: Ceiling Mount

Environmental

ïزئ Operating Temperature: –40 to 70° C (-40 to 158° F) ïزئ Operating Humidity: 20 - 80% Noncondensing

Certification

� CE, FCC, IC

Please visit the Ubiquiti Firmware page for the latest upgrades

### **Please Enquire**