

## Ubiquiti AirCam IP Camera 3 Pack



Product Name: Ubiquiti AirCam IP Camera 3 Pack

Manufacturer: -

Model Number: AirCam-3

Please Note: This product has been discontinued. We recommend the Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-5 as an alternative.

Ubiquiti AirCam IP Outdoor Camera 3 Pack - H.264 megapixel camera

The Ubiquiti AirCam IP Camera 3 Pack is a high performance IP camera with a line of H.264 megapixel camera, which combines advanced industrial design, powerful performance with market leading cost-effectiveness. The Ubiquiti AirCam IP Camera 3 Pack has a number of advanced features which makes the model an ideal solution for video surveillance. Ubiquiti AirCam IP Camera Features

• 1/2 Wall Mount/Ceiling Mount

• 1/2 30 FPS

• 1/2 1MP/HDTV 720p

• 1/2 4.0mm / F1.5

• 1/2 Powered through Ethernet

Included with all units:

• 1/2 Power Over Ethernet Adapter

• 1/2 AirVision UI and NVR Software Installation CD

Ubiquiti Air Cam: Technical Specifications

Camera

• 1/2 Ports: (1) 10/100 Ethernet

• 1/2 Sensor: Progressive Scan RGB CMOS 1/4"

• 1/2 Lens: 4.0mm/ F1.5

• 1/2 Horizontal of View: 47°

• 1/2 Ethernet Ports: Auto MDIX, autosensing 10/100 Mbps

• 1/2 Power LED: Orange

• 1/2 Link/Active LED: Green

• 1/2 Buttons: Factory Reset Button

• 1/2 Maximum Power Consumption: 2.4 Watts

Video

• 1/2 Video Compression: H.264/MPEG-4/MJPEG

• 1/2 Resolution: 1MP/HDTV 720p

• 1/2 Maximum Frame Rate: 30 FPS

• 1/2 Image Setting: Brightness, Contrast, Sharpness, Saturation, 50Hz/60Hz

General

• 1/2 Processor: ARM-based 32-bit RISC

• 1/2 Memory: 128MB DDR2 SDRAM, 8MB Flash

• 1/2 Connector: RJ-45 10BASE-T/100BASE-TX PoE

• 1/2 Maximum Active Array Size: 1280x800

• 1/2 View Angle: 47°; (H), 31°; (V), 54°; (D)

## Ubiquiti AirCam IP Camera 3 Pack

### Network

• Security: Multiple user access levels with password protection, User access log  
• Supported Protocols: IPv4/v6, HTTP, UPnP, DNS, NTP, RTSP, DHCP, TCP, UDP, IGMP, RTCP, ICMP, ARP

### Power

• Power Method: Passive Power over Ethernet (12-24V)  
• Power Supply: 24V/0.5A PoE Adapter included

### Physical

• Dimensions: 158 x 61.5 x 58.5 mm (without mounting arm), 264 x 61.5 x 58.5 mm (with mounting arm)  
• Weight: 240 g (196 g without mounting arm)  
• Mounting: Wall/Ceiling Adapter Kit included

### Environmental

• Operating Temperature: -40 to 70°C (-40 to 158°F)  
• Operating Humidity: 20 - 80% Noncondensing

### Certification

• CE, FCC, IC

Please visit the [Ubiquiti Firmware page](#) for the latest Firmware upgrades  
Also see the [Ubiquiti Aircam Camera Management System](#)

**Please Enquire**