

Aastra 612D DECT IP Phone



Product Name: Aastra 612D DECT IP Phone

Manufacturer: -

Model Number: AAST-612D

Please note: For Aastra DECT Handsets to function, they must be paired with a DECT Base Station such as the Aastra RFP L32, RFP L34 or RFP L35.

Aastra 612D DECT IP Phone

The Aastra 612d DECT IP Phone is ideal for the business sector. The ambient noise filter can automatically adjust the ring tone and talk volume to the background noise in any given situation and filters out any distracting ambient noise. Ensuring optimum communication conditions at all times, especially in loud environments.

Aastra 612D DECT IP Phone Key Features

- 2" Colour TFT display (176 x 220 dots, 65,536 colours)
- Telephone book with 200 contacts (if supported by the PABX)
- Ambient noise filter for loud environments
- 2 programmable navigation keys
- 2 programmable soft keys

With its colour 2" TFT display, the Aastra 612D guarantees an optimum overview and simple operation of the clearly structured menus at all times. It also supports service facilities like firmware download over air1 which helps to reduce support costs. Important events – reminders, incoming call signals, warning of exceeding the system range or indication of battery charge status are all indicated by a 3-colour LED on the handset.

Aastra 612D DECT IP Phone - Technical Specifications

Local Features

- Illuminated keypad
- Different ring tones for: internal and external calls, messages, alarm call, emergency call
- Ring tone volume adjustable
- 3 soft keys for menu control
- Signal tones for key click, confirmation, battery empty, out of range
- Different earpiece-, speaker-, headset volume
- 3 character fonts for text display in different sizes
- Display with 7 text lines, 1 headline and 1 soft key line
- Handset name can be edited
- Display brilliancy adjustable
- Colour scheme can be selected
- Illumination time for display and keypad can be adjusted separately
- Background light of the display can remain on for selectable intervals with dim function
- Alarm and appointment settings for 3 different times each

Adminstration

- Automatic firmware update over air
- Integrated diagnostic functions

Technical Data

- Standards: DECT, GAP
- Ingress protection: IP 50
- Supports DECT encryption

Aastra 612D DECT IP Phone

½ Standard battery (SB): Lithium-Ion battery pack
½ Stand-by-time - Up to 100 h EMEA / 95 h US

Please Enquire
