

## Grandstream GXV3674 HD VF IP Camera (GXV3674\_HD\_VF\_V2)



Product Name: Grandstream GXV3674 HD VF IP Camera (GXV3674\_HD\_VF\_V2)

Manufacturer: -

Model Number: GXV3674\_HD\_VF\_V2

Please Note: This product has been discontinued. Please see the Grandstream GSC3610 Infrared Weatherproof Fixed Dome IP Camera or Grandstream GSC3615 Infrared Weatherproof Wall-mounted Bullet IP Camera as an alternative.

Grandstream GXV3674 HD VF IP Camera (GXV3674\_HD\_VF\_V2)

The Grandstream GXV3674\_HD\_VF is an outdoor HD IP camera with day and night capability utilising both infrared LED and a mechanical IR cut filter. Its weatherproof design with vari-focus High-Definition lens and infrared capabilities provide a superior monitoring solution for outdoor, low-light conditions.

Grandstream GXV3674\_HD\_VF Key Features

- IP66 certified weatherproof casing
- Smart IR to maximise white balance/exposure (IR LEDs can be turned off)
- Includes built-in Power over Ethernet (PoE)
- 1.2 megapixel Progressive Scan CMOS image sensor, 720p resolution
- Features a variable focal lens that can be adjusted from 2.8-12mm
- Supports Motion Detection with up to 16 motion detection target areas
- Supports alert notifications via outbound voice or video call and email screenshot
- SIP/VoIP support for 2-way audio and video streaming to audio, video and mobile phones

The GXV3674 v2 comes equipped with a 3.1 megapixel Progressive Scan CMOS image sensor, capable of 1080p resolution, and supports advanced security features such as motion control and integration to third party speakers, microphones, intercom systems, sirens, alarms and more.

Grandstream GXV3674 HD VF - Technical Specifications

Video Compression

• H.264, JPEG, Motion JPEG

Image Sensor Resolution

• 1.2 Megapixel Progressive Scan CMOS, 1280H x 960V

Image Sensor Sensitivity

• Day/Night mode (exceptional low noise level, low light sensitivity) Shutter: 1/10000 - 1/30 second

Focal Length

• 2.8 - 12 mm

Aperature

• F1.4, DC-IRIS

## Grandstream GXV3674 HD VF IP Camera (GXV3674\_HD\_VF\_V2)

### Field Angle (FOV)

~ 90°; - 28°; (Horizontal Field)

### IR Cut Filter

Yes, Mechanical

### Day & Night Mode

IR LED covering up to 25 meters, with Smart IR software control

### Minimum Illumination

0.05 Lux, 0 Lux with IR

### Responsitivity

5.48V/lux-sec (550nm)

### Pixel Dynamic Range

Wide Dynamic Range of 120dB with SNRMAX 44dB

### Supported Maximum Video Resolution and Frame Rate

1280x960 (25fps); 1280x720 (30fps)

### Video Bit Rate

32 Kbps ~ 8Mbps, Multi-rate for Preview and Recording

### Audio Input

Line-in, 1500 ohms, 0.1 Vrms ~ 0.707Vrms

### Audio Output

Line-Out, 600 ohms, 0.707 Vrms

### Audio Compression

G.711u/a

### Embedded Analytics

Motion Detection (up to 16 target areas)

### Pre/Post Alarm Buffer

8MB

### Snapshots

## Grandstream GXV3674 HD VF IP Camera (GXV3674\_HD\_VF\_V2)

• TCP/UDP/IP, RTP/RTCP, RTSP, DHCP, DDNS, HTTP, HTTPS, SMTP, FTP, NTP

SIP/VoIP Support

• Yes

Power Over Ethernet (PoE)

• IEEE 802.3af, Class 0

Dimensions(D x L)

• 255mm (L) x 104mm (W) x 187mm (H)

Weight

• 1.10kg

Temperature/Humidity

• Operating: -20°C ~ 50°C (-4°F ~ 122°F), 10 ~ 90% RH (non-condensing)

• Storage: -30°C ~ 60°C (-22°F ~ 140°F)

Power Adapter

• Output: 12VDC/1A; Input: 100 ~ 240 VAC, 50 ~ 60 Hz

Casing

• IP66 Compliant Weather-proof Metal Case

Compliance

• FCC Part 15, Subpart B Class B; CE EN 55022 Class B, EN 61000-3-2, EN 61000-3-3 EN 55024, EN 60950-1; C-tick AS/NZS CISPR 22

**Please Enquire**

---