

## OpenVox IPPBX iCallDroid spot



Product Name: OpenVox IPPBX iCallDroid spot

Manufacturer: -

Model Number: iCallDroidspot

OpenVox IPPBX iCallDroid spot

The OpenVox IPPBX iCallDroid spot is the SOHOs IPPBX based on Asterisk. It is an ideal system for small businesses and home offices which require a pint-sized yet powerful on-premise WiFi router IP PBX. OpenVox IPPBX iCallDroid spot Features

- 300M WiFi Router + IP PBX

- Support standard SIP protocols and compatible with multitudinous SIP phones

- Friendly User Interface

- Design for and SOHOs

- Available for OEM

CallDroid spot supports up to 4 concurrent calls with G.729 codec. The compact solid-state device supports 16 extensions and offers a wide range of IP PBX telephony features. iCallDroid spot is based on a low-power but high performance MIPS processor and provides complicated communication features including the hardest HD communication protocol, complete router features and QoS (Ensure the voice quality in a case the bandwidth is not enough). Meanwhile, the feature of one touch to deploy makes the configuration much easier and more enjoyable.

OpenVox IPPBX iCallDroid spot Technical Specification  
Specification Features

- Processor: 580 MHZ MIPS

- 64MB RAM/16MB FLASH

- 1 RJ45 10/100MB Ethernet port WAN

- 4 RJ45 Debug port LAN

- Button: Reset Button, One Touch to auto deploy

- USB2.0 interface

- Internal 2T2R 3dBi

- Power adapter: AC 100~240V input and DC 12V/1A output

- Power consumption: 1.2-2.0W

- Operating humidity: 10~95%

- Operating temperature: 0~45&deg;C

- Size: 3cm\* 10.5cm\* 16cm

- Weight: 350g

IP PBX Features

- Support max 16 SIP extensions, 4 SIP concurrent calls

- Ring Groups/Call Queues/VoiceMail/Follow Me

- Voice Record(only upload the GSM file recording)

- Support IVR voice multi-level menus, buttons to identify and IVR jump function based on time

- Support as many as eight party call conference system and multiple independent conference rooms

- Dial extension intelligence analysis, an extension for BLF support, MWI state

- Audio codec: G.722, G.711U/A, G.729, GSM

- Video codec: H263, H264

- The SIP protocol: based on the TCP/UDP protocol, RFC3261

- Support SIP Trunk: Registration mode, IP trunk mode

- Support route setting and multiple devices cluster processing

- Support background music

- DTMF: In-Band, RFC2833, SIP Info

## OpenVox IPPBX iCallDroid spot

• Support DMZ, uPNP, NAT-PMP

### Network Features

• WAN port: DHCP, Static IP and PPPoE

• LAN port: Static IP only

• Support DDNS

• Support PPTP-VPN, dynamic DNS, firewall, QOS, etc

• Transmitted power: 802.11n 300M 14dBm, 802.11g 54M 16dBm, 802.11b 11M 17-19 dBm

• Support multiple security mode: WEP-Auto, WPA-PSK, WPA-PSK2

• Password type: AES, TKIP

• Diverse international standard time zone

**Please Enquire**

---