

# RTX 8430 DECT Handset



Product Name: RTX 8430 DECT Handset

Manufacturer: -

Model Number: RTX8430Handset

Please Note: This product has been discontinued. Please see the Snom Wireless VoIP Phones for an alternative.

#### RTX 8430 DECT Handset

The RTX 8430 is an entry level wireless DECT Handset featuring a 1.4" TFT display, 2 soft keys and Wideband speakerphone. The 8430 DECT handset supports G.722 codec for HD audio and G726 codec for standard audio.

RTX 8430 Key Features

- � HD audio support (G.722)
- � 1,44'' TFT display, 128x128
- ï¿⅓ Polyphonic ringtones
- � Local phonebook
- � Central phonebook support
- ï¿1/2 Headset connector, 3.5mm
- � Firmware upgradable over-the-air
- ï¿⅓ Wideband speakerphone

# RTX 8830 Technical Specification

Audio

- ï¿⅓ G722 codec for HD audio
- ï¿⅓ G726 codec for standard audio
- ï¿⅓ HD audio speakerphone
- ï¿⅓ HAC compliant

### **TFT Colour Display**

- � 1,44''
- ï¿1⁄2 128 x 128 pixels
- ï¿⅓ 64k colour

#### Keypad

- � 21 keys total
- � 2 soft keys
- � 5-way navigation key
- � ON- and OFF-hook keys
- � Key lock and auto key lock

#### Headset Jack

ï¿1/2 3.5mm, Iphone compliant

### Ringer

- ï¿1/2 5 ringer melodies, 6 levels
- ï¿⅓ Silent ringer
- ï¿⅓ Volume control



# RTX 8430 DECT Handset

تزار Alerting volume, adjustable (low battery, low coverage)

#### DECT

� Frequency bands: 1880 - 1900MHz (EU) 1910 – 1930MHz (LATAM) 1920 –

1930MHz (US)

ï¿⅓ Power levels: 4

ï¿⅓ One antenna

� Encryption supported

� 1 system registration

#### Call Features

i¿½ Call list with 20 entries (All, received, outgoing, missed)

� Redial from call list

ï¿⅓ Speed dial

آذِ½ Central phonebook support (one LDAP server)

� Local phonebook with 50 entries (1 number/name)

� Date and time in Idle display

ï¿⅓ DND support

� CFU/CFB/CFx support

� Call waiting

� Conference call

#### Size and Weight

ï¿1/2 Size: 41 x 135 x 25mm

ï¿⅓ Weight: 108g including batteries

#### Performance

� Talk time: 8h (NB), 7h (WB)

ï¿1/2 Standby time: 75hours

T¿½ Battery type: 2 AAA NiMh, 600mAh T¿½ Range: Indoor: 50m Out-door: 300m

## **Environmental Conditions**

ï¿⅓ IP20 housing

� Operating conditions: 0-40 degrees

### Reliability Spec

ï¿⅓ Drop height: 1m

� Keypad lifetime: 40.000 presses � Keypad abrasion: Standard

#### Charging

� Charge time: 10 hours

ï¿1/2 EU/US/AUS/UK plugs supported

ï¿⅓ Table charging cradle

#### Approvals



ï¿⅓ Radio: EN 301 406

ϊ¿½ EMC: EN 301 489-1 EN 301 489-6

ï¿1⁄2 Safety: EN 60950-1

ï¿⅓ FCC part 15

Price: £91.55