

trixbox Appliance Base



Product Name: trixbox Appliance Base

Manufacturer: -

Model Number: -

Availability: Contact Us for Availability

Rhino Ceros PBX A wide range of Asterisk boxes is available from Rhino. Why not take a look at some of these great value high quality alternatives?

The trixbox Appliance entry point, this package is an all-in-one trixbox solution configured for VoIP telephony. Hardware specifications include an Intel P4 Processor, 512 MB RAM, 80GB Dual HD's with RAID, and dual NIC (onboard network adapter and additional NIC with 4-port switch). trixbox Appliance Base with Intel P4 Processor, 512 MB RAM, 80GB Dual HD's with RAID, and dual NIC

Unlike other telephony appliances, the trixbox Appliance fits into any business. Literally! The trixbox Appliance features 5 different mounting options. From a 19" telephony relay rack mount or cabinet slide-mount, to wall mount and free-standing options, the trixbox Appliance is guaranteed to fit your business needs.

Built for the small and medium business, the trixbox Appliance is not a "mini-appliance." In fact, the trixbox Appliance can scale up to 4 T1s or 48 analogue lines. The trixbox appliance supports Asterisk-compatible cards from virtually any telephony card manufacturer.

Reliability is key for any business, whatever the size. With the dual power supply, the trixbox Appliance Enterprise Edition offers high reliability with the ability to run on multiple power sources; a feature you won't find on any other telephony appliance. In addition, the second hard drive offers data mirroring, ensuring that your data is always safe from a hardware failure.

Featuring two network cards, the trixbox Appliance can be networked in a variety of configurations to meet your specific business needs. To add even more value, one of the network cards features an onboard 4- port switch.

What's that loud noise you hear? It's not your trixbox Appliance! With its intriguing one-of-a-kind custom front panel and limited fan noise, the trixbox Appliance was designed to be seen, not heard.

With a back-lit 4 line LCD included prominently on the front of your trixbox Appliance, you can check the status of the system, including the status of calls and queues, all in a single glance. trixbox Hardware Specifications

• 3U chassis, 19" rack mountable. Mounting options: o 19" telephony relay rack mount o 19" cabinet slide-mount o Wall mount o Free-standing floor o Free-standing tabletop

• 3Ghz P4 1MB Cache

• 512MB RAM (1 GB with Enterprise Edition)

• 80GB 7200 RPM SATA HD's (disk mirroring)

• Dual power supply (Enterprise Edition)

• 2 PCI slots (up to 6 Sangoma cards using Remora expansion cards; system supports 7 full-length bays)

• Dual NIC; one NIC has a 4-port onboard switch

• 4-line LCD display

• 12 month manufacturer's warranty

Please Enquire