

CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom (011304)



Product Name: CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom (011304)

Manufacturer: CyberData Model Number: 011304

CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom (011304)

The CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom (011304) is perfect for settings where either an emergency panic button or two-way priority communications are required.

CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom Key Features

- ï¿1/2 InformaCast compliant
- i¿½ PoE 802.3af enabled (Powered-over-Ethernet)
- ï¿⅓ SIP compliant
- � Adaptive full-duplex voice operation
- � Network web management
- آذِيً Network adjustable speaker volume and microphone sensitivity
- ī¿½ Doubles as a paging speaker: multicast and InformaCast
- ï¿1/2 Network downloadable firmware
- � Concurrent SIP and multicast paging
- � Dry relay contact for auxiliary control (controls external power)
- � Door closure and tamper alert signal
- าั¿½ Supports SRST (Survivable Remote Site Telephony) in a Cisco environment.

One of many within our line of PoE powered VoIP signaling and communication endpoints, the Singlewire InformaCast-enabled VoIP Emergency Intercom has been installed in settings requiring panic buttons and mass notification such as nursing care facilities, schools and universities, daycare facilities and more, proving this device is truly a versatile, cost-efficient alternative to old analog Intercoms. This device supports Singlewire InformaCast notification messaging as well as a true SIP endpoints.

CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom - Technical Specifications Typical Applications

- � Panic button
- � Emergency phone
- ï¿⅓ Mass notification

Modes of Operation

- � Two-way Emergency Intercom
- 12.1/2 Direct call to preset extension (with stored message option)
- ï¿⅓ Multicast broadcast (push-to-talk)
- � Emergency paging speaker

General

- ï¿1/2 Ethernet I/F 10/100 Mbps
- آذِل Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- 12/2 Protocol SIP RFC 3261 Compatible and InformaCast v4.0 and later
- 12.1/2 Operating Temperature -100 C to 500 C (140 F to 1220 F)
- تزير Dimensions 5" x 5" x 2.5" (H x W x D)
- � Warranty 2 years limited
- ï¿1/2 Part Number 011304



CyberData Singlewire InformaCast-enabled VoIP Emergency Intercom (011304)

� Regulatory Compliance FCC Class A, UL 60950 � Payload Types G711, A-law and µ-law

� Operating Temperature

ï¿1/2 Boxed Weight 1.2 lbs.

Price: £550.60