

Akuvox SC-R37 SIP IP Camera



Product Name: Akuvox SC-R37 SIP IP Camera

Manufacturer: -

Model Number: SC-R37

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SC-R37 SIP IP Camera

The Akuvox SC-R37 is suitable for military, government, and medium/large sized enterprises, hospital and other place where there is no sunlight or there are strong light sources at night, and can be installed in strong back-lighting and complex light changing environments.

Akuvox SC-R37 SIP IP Camera Key Features

• 1/3" CMOS sensor with Ultra-Low-Illumination HD Progressive

• Scan Sensor

• Motion Detection

• Frame Rate:

//

/*

//]>

•

//

/*

//]>

• IP66 Grade

Akuvox SC-R37 SIP IP Camera - Technical Specifications Camera

• 1/3" CMOS sensor with Ultra-Low-Illumination HD Progressive

• Scan Sensor

• Minimum Illumination: 0 Lux (IR ON)

• White Balance: Auto/Indoor/Outdoor/ATW

• Aperture Control: Auto/Menu

• Electronic Shutter: 1s to 1/10000s

• AGC: Auto/Menu

• Infrared Parameters: 30m

• Support BLC

• Support D-WDR

Features

• Privacy Masks

• Motion Detection

• Day-night Convert: IR-CUT double filters with automatic switching

• Picture Mirror: On/Off

• Support 3D Digital Noise Reduction

• Video Codec: H.264

• Video Resolutions: 960/720P/D1

• Frame Rate:

//

/*

Akuvox SC-R37 SIP IP Camera

```
// ]>  
&#65292:[email protected]  
//  
/*  
// ]>
```

- Three-stream Encoding: Support setting video parameters independently in each stream
- Audio Coding: G711
- Audio Stream: Bidirectional

Lens

- Interface: CS/Φ;14
- Focal Length: 2.8~12mm (Optional Fixed Focus 4mm，6mm，8mm Lens)

Network

- Supported Protocol: IPv4， TCP/IP， UDP， RTP， RTSP， HTTP，
- ICMP， FTP， SMTP， DHCP， PPPoE，UPnP， IGMP，ONVIF
- Security: User authentication and password protection

Interface

- Alarm: 1 channel alarm input/1 channel alarm output
- Local Output: BNC interface
- Micro SD Card
- Audio Interface: 3.5" audio input interface and audio output interface

Physical Features

- Work Environment: Temp：-20°C～60°C；Humidity: ≤90%
- IP66 Grade
- RJ45 10M/100M, AUTOMDI-X Ethernet
- Power Supply: DC12V/POE Optional
- Power Consumption: 7.5W(MAX，IR ON)
- Dimension: Φ;83(OD)×222(L)mm
- Weight: 1300g

Please Enquire