



# Akuvox SC-R36 SIP IP Camera



Product Name: Akuvox SC-R36 SIP IP Camera Manufacturer: -Model Number: SC-R36

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SC-R36 SIP IP Camera The Akuvox SC-R36 is suitable for military, finance, Electric Power, higher education, medical and other industries where the video surveillance sites require high-definition and low illumination environment. Akuvox SC-R36 SIP IP Camera Key Features

i¿½ 1/3" Progressive Scan CMOS Sensor
i¿½ 1.3MP Real Time Video Output
i¿½ HD 720P Video
i¿½ Three Streams
i¿½ Support PoE
i¿½ 3D DNR
i¿½ ANR

Akuvox SC-R36 SIP IP Camera - Technical Specifications Camera

� 1.3MP Real Time Video Output
� Minimum Illumination: 0 Lux (IR ON)
� White Balance: Auto/Indoor/ Outdoor/ ATW
� Aperture Control: Auto/Menu
� Electronic Shutter: 1s to 1/10,000s
� AGC: Auto/Menu
� Infrared Parameters: 15m
� Support BLC

Features

� Privacy Masks � Motion Detection � Day-night Convert: IR-CUT double filters with automatic switching � Picture Mirror: On/Off � Support 2D/3D Digital Noise Reduction � Video Codec: H.264 � Video Resolutions: 130W/720P/D1 � Frame Rate: [email protected] // /\* // ]]> ,[email protected] // /\*

� Three-stream Encoding: Support setting video parameters � independently in each stream



## Akuvox SC-R36 SIP IP Camera

ï¿<sup>1</sup>⁄<sub>2</sub> Audio Coding: G711 ï¿<sup>1</sup>⁄<sub>2</sub> Audio Stream: Bidirectional

#### Lens

ï¿1/2 Interface: Manual Adjustment of Focus Lens ï¿1/2 Focal Length: 2.8~12mm

#### Network

� Supported Protocol: IPv4,TCP/IP,UDP,RTP,RTSP,HTTP,ICMP ,FTPS,MTP,DHCP,PPPoE,UPnP,IGMP&#6 5292;ONVIF � Security: User authentication and password protection

#### Interface

Alarm: 1 channel alarm input/1 channel alarm output
 Local Output: BNC interface
 Micro SD Card
 Audio Interface: 3.5" audio input interface and audio output interface

**Physical Features** 

� Work Environment: Temp:-20°C~60°C;Humidity: ≤90% � RJ45 10M/100M, AUTOMDI-X EthP,

ï¿1/2 Power Supply: DC12V/POE

ï¿1/2 Power Consumption: 7W(MAX,IR ON)

ï¿1/2 Dimension: Φ145(OD)×106(L)mm

ï¿1/2 Weight: 1300g

### **Please Enquire**