

2N IP Force - 1 Button + Camera + Visual Signalling + RFID Ready + 10W Speaker (9151101CRPW)



Product Name: 2N IP Force - 1 Button + Camera + Visual Signalling + RFID Ready + 10W Speaker

(9151101CRPW)
Manufacturer: -

Model Number: 9151101CRPW

Please Note: This item is no longer available. Please see the 2N IP Force with HD Camera as an alternative.

Please Note: The 2N Intercoms may require additional licenses to activate all features.

Please Note: This unit is RFID ready but does not come with a card reader included. Please see our 2N IP Force Accessories.

2N IP Force - 1 Button + Camera + Visual Signalling + RFID Ready + 10W Speaker (9151101CRPW)

The 2N IP Force 9151101CRPW is an exceptionally sturdy IP intercom that will ensure you effortless communication with the people coming to your door, in combination with reliable security for your building entrance. It supports voice and video communication using the SIP protocol and can deal with the most demanding conditions.

2N Helios IP Force 9151101CRPW Key Features

- آذِ 1/2 The most resistant intercom on the market
- ï¿⅓ High-quality audio
- � Easy remote administration
- ï¿1/2 Access control by a call, code, or card
- � External sources / PoE supply
- 17.1/2 Extensive interface and installation options
- า๊¿1/2 1 button, camera and pictogram card reader ready

The 2N IP Force units are exceptionally tough and resilient with IP65 certification. This means they are perfect for high risk areas that require vandal proof intercoms. 2N IP Force units are commonly used in public access areas, prisons, flats and apartment blocks, hospitals, universities, government offices, car parks and more.

2N Helios IP Force 9151101CRPW - Technical Specifications Mechanical Features

- ī సైస్ట్ Maximal resistivity against dust, water, and mechanical damage
- า๊¿1/2 High clarity and volume in noisy environments
- า๊¿1/2 Illuminated buttons and backlit keyboard
- � Integrated RFID card reader

Benefits

- រ៉េ្ឌ Secure admission to the building of authorised people at selected times
- 17.1/2 Entrance monitoring and following the movement of people
- า๊ะ่½ Interconnecting with other security systems in the building



2N IP Force - 1 Button + Camera + Visual Signalling + RFID Ready + 10W Speaker (9151101CRPW)

i¿1/2 Easy installation and integration into the existing LAN

Target Groups

- � Business: offices, shopping areas
- � Education: universities, campuses, schools, sports areas
- ï¿⅓ Healthcare: hospitals, laboratories
- ī సై Logistics & Logistics & Pransportation: airports, parking lots or garages
- ï¿1/2 Government: prisons
- تزرير Industries: Manufacturing & Production, Energy, Metal & Production, Energy, Energy, Metal & Production, Energy, Energy,

Power Supply

- ï¿1/2 802.3af (PoE) 48 V / 380 mA DC or
- � Adaptor 230 V10%, 50/60 Hz / 12V DC DC power supply 12 V / 1A DC

VolP

- ï¿1/2 Signalization SIP
- ï¿1/2 Number of voice channels 2
- � Audio Codecs G.711, G.729

Interfaces

- าั¿1/2 Ethernet Connector RJ-45 Ethernet speed 10/100 BASE-T
- าั¿½ Reley outputs Maximal voltage 30 V DC, Maximal current 1 A DC

Audio & amp; Video

� Audio 2 integrated microphones, Fullduplex (AEC)

Other

- � Dimensions 217x109x83 mm (h×w×d)
- ï¿1/2 Weight max. 2000 g
- � Operating temperatures from –40 to +55 ºC
- ï¿1/2 Cover level IP65, IP69

Please Enquire