

VTech ErisTerminal VSP725 Entry-Level SIP Phone



Product Name: VTech ErisTerminal VSP725 Entry-Level SIP Phone

Manufacturer: -Model Number: -

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

VTech ErisTerminal VSP725 Entry-Level SIP Phone

The VTech ErisTerminal VSP725 is a business entry-level desk phone. Installation is easy and cost-effective with Power over Ethernet (PoE) support, dual Ethernet ports and auto-provisioning. The VSP725 enables you to program up to 24 buttons for one-touch access to shared call appearances, busy lamp fields, quick dial keys, paging and more.

VTech ErisTerminal VSP725 Key Features

- าั¿½ Advanced call handling, compatible Broadsoft and Asterisk
- � FreePBX support
- าั¿1/2 Flexibility: Support for up to three SIP lines/accounts
- ï¿⅓ Intuitive design
- � One-button call routing: Program up to 12 dual-function feature keys for convenient access, including shared call appearances (SCA), busy lamp fields (BLF), quick dial and feature codes.
- ï¿⅓ Full-duplex speakerphone
- ï¿⅓ HD voice quality
- � Dual Ethernet ports
- � Power over Ethernet
- � Two-year warranty

Manage multiple calls with advanced call handling features and support for up to three SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice guality too.

NOTE: Features and functionality may vary, depending on SIP service provider and/or SIP based PBX equipment.

VTech ErisTerminal VSP725 - Technical Specifications Interface

ï¿1/2 DECT 6.0 RF module embedded

าั¿½ DECT 6.0 (maximum register): 1 cordless headset VSP505

� Dual Ethernet ports - 10/100 Mbps

ī¿½ Base power: adaptor (included) and Class 2 Power over Ethernet (PoE)

Display, Keys and Indicators

ï¿1/2 158 x 57 pixels (w x h) LCD resolution

� LCD backlighting (white)

ï¿⅓ 3 soft keys

ï¿1/2 9 dedicated feature keys

� 24 programmable feature keys (2 pages x 12)

ï¿1/2 4-way navigational pad



VTech ErisTerminal VSP725 Entry-Level SIP Phone

ï¿⅓ Message waiting LED indicator

Audio

- ï¿1/2 Full-duplex base speakerphone
- ï¿⅓ HAC receiver
- � 2.5 mm corded headset jack
- تز 1/2 HD Voice for receiver and speakerphone

Phone Features

- � Supports up to 3 SIP account registations
- ï¿1/2 Local phonebook up to 200 entries
- � Call history up to 200 entries
- � Busy Lamp Field (BLF)
- آذِن Shared Call Appearance (SCA)/Bridged-Line Appearance (BLA) (no. of line)
- ï¿1/2 Do Not Disturb (DND)
- � 3-way local conference
- � N-way network conference
- � Call barring/blocking (block anonymous/blacklist)
- � Dial plan/digit map
- � Call transfer
- � Call hold
- ï¿⅓ Call park
- ï¿1/2 Call pickup
- � Call forwarding: per-line basis (busy/always/no answer)
- � Call timer (call duration)
- าั¿1/2 Phonebook matching(incoming and outgoing calls)
- � Multicast paging
- � Multi-language support
- � Automatic Call Distribution (ACD)

Security

- ï¿⅓ 802.1x
- � 802.1pq
- � Transport Layer Security (TLS)
- ገሪ½ AES encryption of config file for provisioning (128 / 64 / 32 / 16 bits)
- � LLDP-MED

Network

- ۲¿⅓ STUN
- NAT ½'¿ï
- � RTP, SRTP
- SNTP ½ %
- از½ VLAN
- ï¿1/2 Layer 3 QoS (ToS, Diffserv)

Voice CODEC

- ï¿1/2 G.711 a-law & u-law
- � G.722
- ï¿⅓ G.726
- ï¿⅓ G.729



VTech ErisTerminal VSP725 Entry-Level SIP Phone

Provisioning

 $\ddot{\imath}$ 1 2 HTTP, HTTPS, FTP, TFTP

� DHCP options: 66, 159, 160

� Web interface configuration (admin & mp; user)

PnP ½'i

Maintenance

� Diagnostic: pcap trace

ï¿⅓ Syslog

Compatibility

 $\ddot{\imath}$ Broadsoft® Broadworks

ï¿1/2 Asterisk-based platforms

ï¿1/2 Genband™

Warranty

� 2-year warranty

Please Enquire