

## IC-Talk Media Manager MM150r



Product Name: IC-Talk Media Manager MM150r

Manufacturer: IC Talk
Model Number: -

50 User Solid State 1U high 19" rack mount IP PBX...

The MM50 Range is tailored for medium office / large office and is the latest in the product line.

The MM50 is a 1U high 19" rack mountable system which is solid state (no moving parts) and hence is silent in operation. The device is cool running and also shallow depth for convenience. Utilising the latest in solid state flash memory the MM50 can store up to 8 hours of voicemail recordings and 6 months of call details (CDR).

Enterprise class features and up to 50 users make this small format system a real power house with unparalleled capabilities and functions to help make your business perform better, respond quicker and sound more professional.

An extensive list of functions and features coupled with a custom programming interface mean that these systems can be highly integrated into your organisation whilst adhering to the industry standards ensuring you get the best choice of hardware available.

## Features include:-

ï¿⅓ 50 x Extensions

ï¿⅓ 50 x Ring Groups

า๊¿½ 8 Hours of Recording time for voicemails and greetings

i¿½ 6 Months of Call Detail Logging (export to CSV available)

ï¿⅓ 4 x Call Queues

� 4 x Multiway Conference Rooms (pin code protected)

īస్ట్ Choice of PSTN Interface (IPOnly, 4 x ISDN2e or ISDN30e)

ï¿⅓ Unlimited SIP trunks

ï¿⅓ and loads more...

See the full feature list on the bottom right...

Packs all the punch of a larger business phone system, without the cost!

Versions Available

IP Only النظام

17:1/2 Quad ISDN2e - Basic Rate Euro ISDN

(Euro ISDN (300 102) signalling, TE & NT mode operation)

17:1/2 Single ISDN30 - Primary Rate Euro ISDN

(PRI-NET & PRI-CPE, Euro ISDN, NI1&2, 4ESS (AT&T), 5ESS (Lucent) & DMS100)



## IC-Talk Media Manager MM150r

Hardware Specification

Power: 230V AC 50Hz. External Power Adaptor max. consumption 80W (average running consumption 12-25W).

Interfaces: Telephony Slot (varies dependant upon model), 10/100Mb/s Ethernet RJ45 for LAN connection. USB2.0 for Flash Backup Pen.

Protocols: TCP/IP v4 (v6 ready), SIP (Session Initiation Protocol), H.323, IAX2, HTTP1.1 (for administration).

Compression Codecs: ADPCM, G.711 (A-Law & μ-Law), G.726, G.729 (optional extra), GSM, iLBC, Linear, LPC-10 & Speex.

Price: £2,279.05

Options available for IC-Talk Media Manager MM150r:

## **PSTN Connectivity**

Quad ISDN2e (+£712.50), IP Only, ISDN30e (+£712.50), ISDN30e Dual (+£1,282.50).