

## Akuvox SP-R55G IP Phone



Product Name: Akuvox SP-R55G IP Phone

Manufacturer: -

Model Number: SP-R55G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SP-R55G IP Phone

The Akuvox SP-R55G brings high-quality, cost-effective solution to front line staff handling moderate volume of calls through advanced telephony features. The intuitive user interface of the Akuvox SP-R55G makes navigation easy and requires minimal training.

### Akuvox SP-R55G Key Features

- HD Voice
- Up to 3 SIP Accounts
- 2.3" 132\*64 Graphical LCD with Backlight
- Support 3-way Conference
- Support PoE
- 2 Gigabit Ethernet Ports
- Full Compatible with Asterisk, BroadSoft Platform

### Akuvox SP-R55G - Technical Specifications

#### Phone Features

- 3 Lines (support 3 SIP accounts)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable
- Speed Dial, Hotline
- Daylight Saving Time
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (500 groups), Blacklist (100 groups), Call logs (100 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Languages Support

#### IP-PBX Features

- SMS.Voicemail.MWI Message Notification
- Music on hold, Intercom
- BLF (Busy Lamp Field)
- Call Pickup, Group Call Pickup
- Call Recording
- Anonymous Call, Anonymous Call Rejection

## Akuvox SP-R55G IP Phone

### Audio Features

- HD Voice
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_16, G726\_24, G726\_32, G726\_40
- VAD, CNG , Echo Cancellor
- Full-Duplex Speakerphone

### Security Features

- Support HTTPS (SSL)
- Support SRTP for Voice Data Encryption
- Support Login for Administration
- SIP Over TLS

### Network Features

- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP con guration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1Q VLAN

### Administration Features

- POWER
- POE 802.3af/802.3at
- 48VDC input

### PHYSICAL CHARACTERISTICS

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Manamements with web,keypad on the phone,and Auto Provisioning
- SNMP
- TR069

### Physical Features

- Audiocodes Chipset
- 2.3" 132\*64 Graphical LCD with Backlight
- 34 Keys (with 4 Soft Keys)
- 4 LED Lights (1 Power Light, 3 Account Lights)
- RJ9 Handset Jack and Headset Jack
- 2 RJ45 10/100/1000M Ethernet Jacks
- RJ12 Expansion Socket
- AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- PoE: IEEE 802.3af
- Giftbox Size:202\*239.5\*102.5 (mm),weight: 1.19 kg

## Akuvox SP-R55G IP Phone

**Please Enquire**

---