



Product Name: AVer EVC150 HD Video Conferencing Endpoint

Manufacturer: -

Model Number: EVC150

Please Note: This product is no longer available. To find an alternative, please see our IP Video Conferencing solutions.

AVer EVC150 HD Video Conferencing Endpoint

The AVer EVC150 is video conferencing's price-to-performance leader, offering small to medium-scale organizations a uniquely cost-effective full HD video conferencing solution. The EVC150 features real-time full HD video streaming and HD 720p content sharing along with a PTZ camera, an microphone array, a sleek UI and a compact system design. In addition to its impressive hardware, the EVC150 comes with a 3-year standard warranty and remarkably low total cost of ownership, translating into an astounding return on investment. Whether for point-to-point conferencing, cloud-based video collaboration or hardware system integration, the standards-based EVC150 is the system of choice for savvy VC users.

AVer EVC150 Key Features

Τ¿½ Full HD video & Description on one monitor at HD 1080p 30fps, while sharing presentation files, animation, visualizer images and more on another at HD 720p 30fps, creating a smooth, interactive video conferencing experience.

ī¿½ One-touch recording - Record your video conferences- including video, audio and shared content- directly to a USB flash drive, creating video archives and helping avoid post-meeting information loss. Play back recorded meetings using your EVC150, or on your PC using AVer's VCPlayer software.

ī¿½ PTZ camera with 18X total zoom - The EVC150's powerful full HD PTZ camera offers 12X optical zoom plus 1.5X digital zoom, as well as +/-130° pan and +90°/-25° tilt, quick auto-focus and clear close-ups of participants, making it ideal for any size of conference room.

ϊ¿½ Connect up to 4 microphones via daisy-chain - The EVC150's all-new microphone array and codec employ an array of sophisticated audio processing technology, such as advanced noise reduction, automatic gain control and echo cancellation, producing crisp, true-to-life sound even better than previous AVer systems.

ϊ¿½ Remarkable 100 camera presets - No need to waste time panning and zooming manually during EVC150 video conferences – simply program its presets on the remote control ahead of time, and during meetings you can shift the camera from a wide view of the room to a close-up of an object with just the press a button.

� Handy integration & premote access tools - Access EVC150 remotely and troubleshoot issues using WebTool, AVer's web-based management platform, and leverage advanced network technology Wake-on-LAN (WOL), Telnet, network test, and HELPeRTM to make the EVC150 the perfect device for integration via LAN or the internet.

AVer EVC150 - Technical Specifications Package Contents

� Main system unit (codec)

� The New eCam PTZ camera

� EVC microphone array

� IR remote control with batteries

� Power supply

� Cables

ï¿⅓ Warranty card



ï¿1/2 Quick guide

Communications

ï¿1/2 H.323, SIP and SIP TLS standards

ï¿⅓ 64Kbps~4Mbps

ï¿1/2 RJ45 network LAN (10/100/1000)

ï¿1/2 Manual bandwidth settings

Camera

ï¿1/2 Support for single camera*

� The New eCam PTZ camera: - 2-mega pixel CMOS sensor - 18X total zoom (12X optical + 1.5X digital zoom) - ±130° pan; +90°/-25° tilt - Field of view (H): 72° - Field of view (V): 43° - Field of view (Diagonal): 82°

People Video Resolutions

� HD1080p (1920 x 1080)

ï¿⅓ HD720p (1280 x 720)

� 480p (848 x 480)

� 4CIF (704 x 576)

� 4SIF (704 X 480)

� 360p (640 X 360)

� W288p (512 x 288)

� CIF (352 x 288)

ï¿% SIF (352 X 240)

ï¿1/2 All resolutions at 30fps

Content Video Resolutions

� Supported Resolutions: - WSXGA (1440 x 900) - HD (1360 x 768) - SXGA (1280 x 1024) - SXGA (1280 x 960) - WXGA (1280 x 800) - XGA (1024 x 768) - SVGA (800 x 600) - VGA (640 x 480)

� Output Resolutions: HD720p (1280 x 720) up to 30fps

Video Standards

 \ddot{i} \dot{i} \dot{i}

ï¿⅓ H.239 dual video streams

ï¿1/2 BFCP content sharing

Video Inputs

� EVC eCam camera

ï¿⅓ VGA

Video Outputs

ï¿⅓ HDMI

� VGA

Audio Standards

� G.711, G.722, G.722.1, G.728, G722.1C licensed from Polycom®



Audio Features

� Automatic gain control (AGC)

� Advanced noise reduction

� Acoustic echo cancellation (AEC)

Audio Inputs

� EVC microphone daisy chain up to 4

� Line-in (3.5 mm)

Audio Outputs

ï¿1/2 Digital audio on HDMI cable

� Line-out (3.5 mm)

Other Supported Standards

� H.224, H.225, H.245, H.281, H.323 Annex Q, H.460

User Interface

� Multiple layout styles

ϊ¿½ User-friendly OSD (22 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish) Τέ½ Display/edit site name

Network

� 10/100/1000Mbps

� NAT/firewall traversal

آزٰ High Efficiency Lost Packet Recovery (HELPeR™)

� API support via Telnet

ï¿1/2 Wake-on-LAN (WOL) support

ï¿1/2 IPv4 and IPv6 support

QoS

ï¿⅓ Network Test

Security

าั¿½ AES (Advanced Encryption Standard) function (128-bit)

ï¿1/2 Password protection for system settings

12/2 Password protection for remote system management

Web Management Tool

� Remote management through the Web

ï¿1/2 Live monitoring via the web

� Firmware update via Ethernet/Internet

� Phonebook download/upload/edit

� Restore system settings

Value-Added Features



� Meeting Recording - In meeting and offline recording - Save directly to USB flash drive - Supports screen re-layout during playback - Playback and file conversion via VCPlayer software (.mov/.mp4 format)

ï¿1/2 Speed dialing via hot keys (10 sets)

� camera presets (10 positions)

� Network Time Portocol (NTP)

ï¿1/2 ScreenShare support

ï¿⅓ VCLink support

Power Supply

� AC 100V~240V, 50/60Hz � Consumption: EIAJ 12V, 4A

Physical Characteristics

� Package dimensions: 376 x 300 x 243 mm

ï¿1/2 Package weight: 6.49kg/14.31lbs

ï¿1/2 Main system (codec): 260 x 158.7 x 33 mm

� New eCam PTZ camera: 180 x 144 x 184 mm

� EVC microphone array: 131.9 x 118.6 x 25.5 mm

Optional Accessories

ï¿1/2 Additional microphone

� eCam camera mount

ï¿1/2 Replacement eCam Focus camera

Warranty

ï¿⅓ 3-year standard warranty**

* Only one camera can be used at a time. ** For detailed warranty information, please contact an AVer representative.

PHYSICAL CHARACTERISTICS

ï¿1/2 POWER POE 802.3af/802.3at 48VDC input

Please Enquire