

Akuvox SVG6004 4 FXS VoIP Gateway



Product Name: Akuvox SVG6004 4 FXS VoIP Gateway

Manufacturer: -

Model Number: SVG6004

Please Note: The Akuvox SVG6004 4 FXS VoIP Gateway has been discontinued. Please see our VoIP Gateways page for alternative products.

Akuvox SVG6004 4 FXS VoIP Gateway

The Akuvox SVG6004 VoIP Gateway is designed for voice and fax services in IMS/soft-switch network of Telecom Carrier or VOIP service provider's network. It follows SIP/MGCP/H.248 protocol. SVG6004 offers 4 analog FXS ports to meet different needs of users. With the priority of forwarding voice packages, it can provide excellent QoS.

Akuvox SVG6004 Key Features

- าั¿1/2 Communication Protocol Follows SIP/MGCP/H.248 protocol
- ī¿½ QoS Guarantee The port-based priority control makes voice packages transmitted first to provide excellent QoS

� High Quality Voice Supports multiple voice quality techniques, such as dynamic voice jitter buffer, VAD, CNG, echo sound offset and packet loss compensation, to provide high-quality voice as that of traditional telephones

Akuvox SVG6004 Technical Specification General

- าั¿½ Protocol SIP RFC3261 MGCP H.248 SDP RFC2327 RTP/RTCP
- ï¿1/2 SIP SIP Trunk SIP Register
- ї¿1/2 Codec G.711A/G.711U/G.723.1/G.729A/G.729AВ
- T¿½ Voice Enhancement G.165/G.168 echo cancellation Dynamic Jitter Buffer VAD/CNG Packet Loss Compensation
- تزار DTMF In-Band DTMF / RFC2833 / SIP Info
- FAX T.38 T.30
- า๊¿½ Network Static IP / DHCP Client / DNS / SNTP
- � QoS 802.1Q VLAN 802.1p Priority IP Tos
- آذِالِدُ NAT Traversal Static NAT Configure SIP Keep Alive Register STUN
- ï¿1/2 Configuration WEB Browser Console/Telnet
- $\ddot{i}_{\dot{c}}$ Firmware Upgrade FTP / HTTP Network Interface Four 10/100Mbps Auto-negotiation RJ45 ports supporting Auto MDI/MDIX
- ï¿1/2 Analog Interface 4 FXS(RJ11)
- Ti,1/2 Power AC adapter input: 100~242AC, 48/60Hz Consumption: <50W
- T¿½ Environmental Conditions Operating temperature: 0°C~40°C Storage temperature:
- -20°C~60°C Humidity: 20~90%, non-condensing
- تزير Dimensions and Weight Size:250(W) ×47(D) ×188 (H) mm Net Weight: 1.8kg

Please Enquire