

Spectralink 7212 DECT Handset



Product Name: Spectralink 7212 DECT Handset

Manufacturer: Spectralink

Model Number: 0261 0000

Please Note: Spectralink Dect Handsets require a charging station and PSU which are not included with the handset. These can be added to your order via the drop down menu above. If you require other options please see the Spectralink Accessories sections.

Spectralink 7212 DECT Handset

The Spectralink 7212 is designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature rich 7212 makes it a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handsets to be customised to specific vertical markets.

The Spectralink 7212 Key Features

- 1/2 Colour display
- 1/2 Date and time in display*
- 1/2 Auto key lock
- 1/2 12 different ringtones and adjustable ring volume
- 1/2 Special ring tones for noisy environments
- 1/2 Auto login – roaming between two different installations
- 1/2 Auto-answer (B-answer)
- 1/2 Alarm key – ready for alarm application**
- 1/2 Alarm key speed dial
- 1/2 CLIP
- 1/2 Telephone book with 50 entries
- 1/2 Call list of incoming/missed/received calls (up to 40 calls)
- 1/2 Text message
- 1/2 LED indication of incoming and unanswered calls
- 1/2 Full Slot DECT radio
- 1/2 Software Update Over The Air (SUOTA)
- 1/2 14 menu languages (UK, FR, DE, ES, IT, NL, CZ, PL, DK, NO, SV, FI, PT, RU)

The Spectralink 7212 extends the capabilities of the Spectralink 7202. With the possibility of attaching a headset, it allows users to enjoy hands-free mobility.

The Spectralink 7212 Technical Specification

APPROVALS

- 1/2 EMC: – EN 301 489-1 – EN 301 489-6

SIZE AND WEIGHT

- 1/2 Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.)
- 1/2 Weight: 123 g incl. battery (4.3 oz incl. battery)

SPEECH / STANDBY TIME

- 1/2 Speech time: up to 23 (27 hours in economy mode)
- 1/2 Standby time: up to 118 hours

BATTERY

- 1/2 Battery: NiMH battery

Spectralink 7212 DECT Handset

- Easily removable battery with option to use in shift operation environments
- Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

TEMPERATURE

- Operating temperature: 0 - 40°C (32°F - 104°F)
- Charging temperature: 0 - 25°C (32°F - 77°F)

IP RATING

- 7212: IP 54

TESTS

- Bump test: IEC 68-2-29

Price: £192.90

Options available for Spectralink 7212 DECT Handset :

Spectralink Charger for 72 and 76 Series

[Not Required](#), [Required \(+£13.00\)](#).

Spectralink UK PSU for Charger

[Not Required](#), [Required \(+£13.90\)](#).

Spectralink Dual Charger & slot for spare battery

[Not Required](#), [Required \(+£54.00\)](#).