

Escene IS730 IP Intercom



Product Name: Escene IS730 IP Intercom

Manufacturer: Escene

Model Number: IS730

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil or 2N range.

Escene IS730 IP Intercom

The Escene IS730 IP Door Phone is compatibility with different platforms, offering users a convenient service. The Escene IS730 is dust proof, water proof and has dismantle prevention. The IS730 enables door opening by long-distance DTMF, Password. Its powerful performance, stability and reasonable price make it a perfect choice for industry users.

Escene IS730 Key Features

- Supports embedded or wall-mounted installation.
- High-fidelity sound quality, HD codecs, Full duplex hands-free calls;
- WEB supports multi-language: Chinese, Russian, French, etc.
- 1 SIP accounts, support 3-way conferencing;
- 1*RJ45 standard Ethernet Ports(LAN), Support PoE;
- Digital Keyboard, can provide dial-up or password input;

NOTE: IS730-PT, P is POE, T is Touchpad.

Escene IS730 - Technical Specifications

Phone Features

- WEB Support Multi-language
- Support 1 Lines Talking
- DND, Hot line
- Auto-answer, 3-way conferencing
- Direct IP call without SIP proxy
- Custom DSS Key(Speed Dial / Intercom,etc)
- Time setting(SNTP/SIP Server/Manual)
- Full-duplex Talking, Dial with digital keypad
- Support switching SIP server & Second server
- WEB Volume control

Advanced Features

- Built-in Indoor-open interface
- Built-in External Power interface
- Built-in Relay
- Open the Door ways:DTMF/PWD

Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711μ/A, G.723.1
- G.726, G.729AB,VAD, CNG, AEC, AGC
- Full-duplex,

Network Features

Escene IS730 IP Intercom

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode, DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server

Physical Features

- 1*Digital Keypad, backlit digital (Option)
- 1*Speaker Key or DSS key
- 1*RJ-45 10/100M(LAN)
- Support PoE: IEEE802.3af class 0
- Embedded or wall-mounted installation
- Power: 12V/1A DC
- Minimized Power:4W
- Maximum Power: 6W
- Operating humidity: -30~60°C
- Storage temperature: up to 60°C
- Relative Humidity:10-90%

Please Enquire