

Escene IS720 IP Intercom



Product Name: Escene IS720 IP Intercom

Manufacturer: Escene

Model Number: IS720

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil or 2N range.

Escene IS720 IP Intercom

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

The Escene IS720 IP Door Phone has a professional design and meets the requirements of industry users. The IS720 is dust proof, water proof and has dismantle prevention. The IS720 enables door opening by long-distance DTMF, Password and RFID. With powerful performance, stability and reasonable price, the IS720 is a perfect choice for industry users.

Escene IS720 Key Features

- Supports embedded or wall-mounted installation
- High-fidelity sound quality, HD codecs, Full duplex hands-free calls;
- WEB supports multi-language: Chinese, Russian, French, etc.
- 2 SIP accounts, support 3-way conferencing;
- 2*RJ45 standard Ethernet Ports(LAN/PC), Support PoE;
- Backlit Digital Keyboard, can provide dial-up or password input(Optional);
- *Built-in RFID reader; Indoor open-door interface and external power supply interface;
- User-defined DSS keys, which can be set up to Speedy dial, intercom,etc.
- Supports Plug-and-Play, auto-provision, remote maintenance and management;

NOTE: IS720-PRT, P is POE, R is Reader(optional), T is Touchpad(optional).

Escene IS720 - Technical Specifications

Advanced Features

- Built-in RFID Reader
- Built-in Indoor-open interface
- Built-in External Power interface
- Built-in Relay
- Open the Door ways:DTMF/PWD/RFID Card
- SN-SG Log, Remote access list
- Support RFID Card

IP PBX System Integration

- DND&Call Transfer
- Intercom, Paging
- Anonymous call, Anonymous call rejection
- Network conference, Distinctive ring tone,
- Call pickup, Dial Plan, Call recording
- Intercom, Paging, Music on hold

Codes and Voice Features

Escene IS720 IP Intercom

- Wideband Codec: G.722
- Narrowband codec: G.711μ/A, G.723.1
- G.726, G.729AB, VAD, CNG, AEC, AGC
- Full-duplex,

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode,
- DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- SNMP V1/2 , TR069
- Configuration: browser/phone/auto-provision
- Trace package and system log export

Security

- 802.1x, VLAN QoS (802.1pq)
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection

Physical Features

- 1*Digital Keypad, backlit digital (Option)
- 1*Speaker Key or DSS key
- 1*Power Light, 1*Network&SIP Light
- 1*Talking status light
- 2*RJ-45 10/100M(LAN/PC)
- Support PoE: IEEE802.3af class 0
- Embedded or wall-mounted installation
- Power: 12V/1A DC
- RFID/ IC Card
- Minimized Power:4W
- Maximum Power: 6W
- Operating humidity: -30~60℃
- Storage temperature: up to 60°C
- Relative Humidity:10-90%

Package Features

- Qty/CTN: 20PCS
- N.W/CTN: 9.4KG

Escene IS720 IP Intercom

• G.W/CTN: 12KG
• Measurement: 0.068CBM(0.5% more or less)
• Dimension: 162X112X41MM
• Carton Meas: 365X365X270MM
• Admin/User 2-level configuration mode

Please Enquire
