

DrayTek VigorBX 2000 IP PBX & DSL Firewall



Product Name: DrayTek VigorBX 2000 IP PBX & DSL Firewall

Manufacturer: -

Model Number: vigorbx-2000

DrayTek VigorBX 2000 IP PBX & DSL Firewall

The VigorBX 2000 is an IP PBX integrated with the firewall/router features of DrayTek's Vigor 2860 ADSL/VDSL router. As an IP PBX, instead of conventional phone lines, Internet SIP trunks provide your connectivity to the phone network. With IP phones, you have a complete office phone system, allowing for local and remote extensions (extensions can be anywhere on your LAN or elsewhere in the world).

DrayTek VigorBX 2000 Key Features

- Voice-over-IP PBX
- VDSL2/ADSL2+ Firewall/Router
- 6-Port Gigabit Ethernet LAN Switch
- Multiple Private LAN Subnets & VLANs
- QoS (Layer 2 & 3, 802.1p & TOS/DCSP)
- PBX Features Include:

- Up to 50 VoIP Extensions (local or remote)
- 2 x FXO Port (Analogue Line Interface)
- FXS Analogue Phone Interface (with POTS failover)
- Voicemail (with remote & email access)
- Call Queuing
- Multi-Level IVR (Voice Auto-Attendant)

- VPN for LAN-to-LAN or teleworkers
- 802.11ac WiFi ('VigorBX 2000ac' only)
- Optional VigorCare Available
- Free Windows Softphone included
- Rack-mountable (Optional 'RM1' required)

Calls can be transferred and distributed exactly as you wish, routed to a receptionist, groups or an automated attendant (IVR - "Press 1 for Sales" etc.) or to specific groups. The VigorBX 2000 supports up to 50 extensions, all with voicemail.

The VigorBX 2000 offers a complete replacement to the traditional office phone system and analogue lines. An IP-PBX uses your existing network and the Internet to provide company-wide telephony, using VoIP technology instead of regular phone lines or a traditional PBX. This can save hugely on line rental, provides vast flexibility, reduces call costs, maintenance and increases efficiency. IP Phones can be placed anywhere in your office, or remotely around the world to provide one seamless phone network for your business. Wherever you have an Internet connection, you can have an extension on your PBX. All pure IP calls are free of charge; for calls to the conventional phone network (PSTN) you route via an ITSP 'Trunk' for low cost calls.

In a pure IP environment, the VigorBX 2000 is installed onto your LAN together with IP telephones. All devices are connected over your LAN using your existing Ethernet network connections. The VigorBX 2000 can support up to 50 extensions - local or remote. As it uses your regular network, you don't need special extension wiring - just your existing Ethernet switch with adequate ports (assuming you are using IP phones). A traditional PBX with 50 extensions would take up a whole cabinet and need a lot of wiring!

Once installed, all extensions can call each other of course and calls can be transferred, diverted and all other normal features of a PBX. Extensions do not have to be local (in the same office as the iPBX) - they can be anywhere in the world, and still be seamless so that calls can be made between to transferred to extensions whether they are local or remote. Similarly, incoming calls

DrayTek VigorBX 2000 IP PBX & DSL Firewall

can be routed to any extensions, whether they are local or distributed in many remote locations - anywhere with an Internet connection. As well as physical desk phones and cordless phones, you can also use softphones running on your laptop or IP phone apps on your smartphone.

DrayTek VigorBX 2000 - Technical Specifications

Physical Interfaces

• 1/2 LAN Ports (Switch)

• 1/2 6 X Gigabit Ethernet (1000Mb/s) Ports

• 1/2 WAN Ports:

• 1/2 WAN1 : ADSL2+/VDSL2 RJ11, supports G.INP & Vectoring (UK Models)

• 1/2 WAN2 : Gigabit Ethernet (1000Mb/s) Ethernet for load balance and WAN failover

• 1/2 WAN3 : USB 2.0 Port for 3G / 4G / LTE Cellular Modem

• 1/2 WAN4 : USB 2.0 Port for 3G / 4G / LTE Cellular Modem

• 1/2 2 x USB 2.0 Port for 3G / 4G / LTE or Printer, USB Storage or USB Thermometer

• 1/2 VoIP Ports:

• 1/2 1 X FXS Analogue Telephone Port

• 1/2 2 X FXO Analogue Line Port

FXS Port Features

• 1/2 Call Hold/Retrieve

• 1/2 Call Waiting with Caller ID

• 1/2 Call Transfer

• 1/2 Call Forwarding (Always, Busy, No Answer)

• 1/2 Hotline

• 1/2 PSTN Pass-through (FXO1) when power failure

• 1/2 PSTN Pass-through when Internet connection dropped/Registry failure

VoIP Protocols

• 1/2 SIP, RTP/ RTCP

• 1/2 G.168 line echo-cancellation

• 1/2 Automatic gain control

• 1/2 Jitter buffer (180ms)

• 1/2 Voice codecs : G.711, G.723.1, G.726

• 1/2 VAD/CNG

• 1/2 DTMF tone : Inband / Outband (RFC-2833) / SIP Info

• 1/2 FAX/Modem support : Tone detection / G.711 pass-through / T.38 for FAX

LAN Features

• 1/2 6 X LAN Subnets, IP Routed Subnet & DMZ Subnet

• 1/2 Port-Based or 802.1q VLAN Tag-Based VLAN

• 1/2 LAN Port Mirror

• 1/2 Wired 802.1x

• 1/2 IPv6 Multi-Subnet LAN1-6 & DMZ Subnet

DrayTek VigorBX 2000 IP PBX & DSL Firewall

1/2 Routing or NAT mode for LAN 2-6 & DMZ Subnet

Please Enquire
