



Akuvox R27P IP Door Phone

1	
1	
1	
1	(0)
1	
1	

Product Name: Akuvox R27P IP Door Phone Manufacturer: -Model Number: R27P

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox R27P IP Door Phone

The Akuvox R27P IP Door Phone security that comes with beeing able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R27P enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure. Akuvox R27P Key Features

ï¿1/2 Vandal resistant body, with flush buttons

ï¿1/2 Wild-angle camera: 110º

ï¿1/2 PoE (IEEE802.3af, Power-over-Ethernet);

ï¿1/2 Two-way audio communication over IP networks with Echo Cancel feature;

i¿1/2 Complies with SIP standard for easy integration in every SIP capable PBXes;

Akuvox R27P - Technical Specifications Physical & amp; Power

ï¿1/2 Body material: all-aluminum

ï¿1/2 Camera: 3M pixels, automatic lighting

ï¿1/2 Numeric keypad with extra buttons

ï¿1/2 Infrared Sensor: Optional

ï¿1/2 RF Card Reader: Optional

ï¿1/2 Output Relay: 2 output relays for door opener

ï¿1/2 802.3af Power-over-Ethernet

ï¿1/2 12V DC connector (if not using PoE)

ï¿¹/₂ Power consumption: less than 12W

- ï¿1/2 Water-proof & amp; Dust-proof: IP65
- ï¿1/2 Installation: Wall-mounted

ï¿1/2 Dimension: 250x140x35mm

SIP Endpoint

ï¿¹/₂ SIP v1(RFC2543), SIP v2(RFC3261)

� Audio codecs: G.711a, G.711μ, G.722, G.729

ï¿1/2 Video codecs: H.263, H.264

ï¿1/2 Speech Quality: 7kHz Audio

ï¿1/2 Echo Cancellation

ï¿1/2 Voice Activation Detection

ï¿1/2 Comfort Noise Generator

Video

ï¿1/2 Resolution: up to 1080p

ï¿1/2 Maximum image transfer rate: 1080p - 30fps

i¿1/2 High intensity white LEDs for picture lighting during dark hours with internal light sensor

i¿1/2 Compatible to 3rd-Party-Video components, e.g. NVRs



Akuvox R27P IP Door Phone

Door Entry Features

- ï¿1/2 Relays controlled individually by DTMF tones
- $\ddot{\imath}_{{\it i}}{\it i}_{{\it 2}}$ Camera permanently operational W
- ï¿1/2 hite balance: auto
- $\ddot{\imath}_{2}^{1/_{2}}$ Auto-night mode with LED illumination
- ï¿1/2 Minimum illumination: 0.1LUX

Networking

i¿½ 1x10/100 Mbps Ethernet port i¿½ Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Application Scenarios

i¿½ Office door phone with on-site or hosted IP-PBX i¿½ Remote site entry over Internet i¿½ Apartment/flat intercom with door access control

Please Enquire