

## Escene 720PT IP Security Intercom



Product Name: Escene 720PT IP Security Intercom

Manufacturer: Escene

Model Number: 720PT

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil or 2N range.

Escene 720PT IP Security Intercom

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement

The Escene 720PT is a door intercom that is dust proof, water proof and also has dismantle prevention, supporting 2 SIP accounts and 3 way conferencing. The Escene 720PT can either be embedded or mounted onto a wall, and has high fidelity sound.

Escene 720PT Key Features

- Support embedded or wall-mounted installation.
- High-fidelity sound quality, HD codec, Full duplex hands-free calls;
- WEB supports multi-language: Chinese, Russian, French, etc.
- 2 SIP accounts, support 3-way conferencing;
- 2\*RJ45 standard Ethernet Ports(LAN/PC), Support PoE;
- Backlit Digital Keyboard, can provide dial-up or password input(Option);
- User-defined DSS keys, which can be set up to Speedy dial, intercom,etc.
- Support Plug-and-Play, auto-provision, remote maintenance and management

Escene 720PT Technical Specification

Phone Features

- WEB Support Multi-language
- Support 2 Lines Talking
- DND, Hot line
- Auto-answer, 3-way conferencing
- Direct IP call without SIP proxy
- Custom DSS Key(Speed Dial / Intercom,etc)
- Time setting(SNTP/SIP Server/Manual)
- Full-duplex Talking, Dial with digital keypad
- Support switching SIP server & Second server
- WEB Volume control

Advanced Features

- Built-in RFID Reader
- Built-in Indoor-open interface
- Built-in External Power interface
- Built-in Relay
- Open the Door ways:DTMF/PWD/RFID Card
- SN-SG Log, Remote access list
- Support RFID Card

IP PBX System Integration

- DND&Call Transfer

## Escene 720PT IP Security Intercom

- Intercom, Paging
- Anonymous call, Anonymous call rejection
- Network conference, Distinctive ring tone,
- Call pickup, Dial Plan, Call recording
- Intercom, Paging, Music on hold

### Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711&mu;/A, G.723.1
- G.726, G.729AB,VAD, CNG, AEC, AGC
- Full-duplex,

### Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode,
- DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server

### Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- SNMP V1/2 , TR069
- Configuration: browser/phone/auto-provision
- Trace package and system log export

### Security

- 802.1x, VLAN QoS (802.1pq)
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

### Physical Features

- 1\*Digital Keypad, backlit digital (Option)
- 1\*Speaker Key or DSS key
- 1\*Power Light, 1\*Network&SIP Light
- 1\*Talking status light
- 2\*RJ-45 10/100M(LAN/PC)
- Support PoE: IEEE802.3af class 0
- Embedded or wall-mounted installation
- Power: 12V/1A DC
- RFID/ IC Card
- Minimized Power:4W

## Escene 720PT IP Security Intercom

- Maximum Power: 6W
- Operating humidity: -30~60&#8451;
- Storage temperature: up to 60&deg;C
- Relative Humidity:10-90%

### Package Features

- Qty/CTN: 20PCS
- N.W/CTN: 9.4KG
- G.W/CTN: 12KG
- Measurement: 0.068CBM(0.5% more or less)
- Dimension: 162X112X41MM
- Carton Meas: 365X365X270MM

**Please Enquire**

---