

CyberData Singlewire InformaCast VoIP Speaker (011396)



Product Name: CyberData Singlewire InformaCast VoIP Speaker (011396)

Manufacturer: CyberData

Model Number: 011396

CyberData Singlewire InformaCast VoIP Speaker (011396)

The Cyberdata SingleWire Informacast Speaker 011396 is for use with Singlewire's paging and emergency notification software InformaCast or InformaCast CK.

Cyberdata 011396 Key Features

- Protocol InformaCast®; and/or SIP
- Ethernet I/F 10/100 Mbps
- Power Input PoE 802.3af/802.3at
- Operating Temperature -10 degrees C to 50 degrees C (14 degrees F to 122 degrees F)
- Payload Types G.711 μ-law, G.711 a-law, and G.722 + Singlewire HD
- Output Level 10 Watts Peak Power
- Sensitivity 96dB / 1W / 1M S.P. Level
- Dimensions 9" x 2.4"
- Warranty 2 Year Limited
- Part Number Standard Color 011395, RAL 9002, Gray White (replaces 011102)
- Part Number Optional Color 011396, RAL 9003, Signal White (replaces 011103)

This device is a PoE-powered IP Speaker that registers easily to new and existing Singlewire installations. It can also register with Cisco Call Manager as a SIP end point using a Cisco SIP License.

Cyberdata 011396 Technical Specification

SIP Features

- Dual registration for Singlewire and SIP
- Support for security code to prevent unwanted SIP calls
- Optional red/green/blue/white strobe kit connection available (coming soon)
- Autoprovisioning via HTTP, HTTPS, or TFTP
- HTTPS or HTTP web based configuration. HTTPS is enabled by default.
- 802.11q VLAN tagging
- Configurable sense input for use with fault detection or with optional lighted button kit
- Configurable event generation for device health and status monitoring
- Support for G.722 codecs.
- Powered via PoE (802.3AF or 802.3AT) or 24V auxiliary power supply
- Enhanced interoperability for hosted environments
- SIP (RFC 3261) compatible
- Night Ringer function
- Plays audio from Multicast
- Web-based configuration
- Paging prioritization and background music
- User upgradeable firmware via web interface or autoprovisioning
- External volume control
- Small footprint
- High efficiency speaker driver
- IGMP I SIP endpoint or Multicast group member
- Network-adjustable speaker volume
- Can drive one external analog speaker for greater coverage (part #011120/011121 sold separately)
- Optional clock kit available (part #011153/011154 sold separately)
- Support for 10 multicast paging groups
- Support for multiple SIP servers for redundancy

CyberData Singlewire InformaCast VoIP Speaker (011396)

- Support for Cisco SRST resiliency
- Relay for activating door locks, external amplifiers, etc.
- Line-level audio output for connecting to an external amplifier

Singlewire InformaCast Features

- Singlewire Informacast compatibility available. Includes support for Informacast resiliency.
- Supports both SIP and Singlewire InformaCast
- InformaCast compliant
- InformaCast CK compliant

Price: £473.70
